

ORDINANCE NO. 1414

AN ORDINANCE AUTHORIZING A CONTRACT BETWEEN THE CITY OF CANBY AND ALTEC INDUSTRIES, INCORPORATED FOR THE PURCHASE OF A MODEL AT 40-G ARTICULATING/ TELESCOPIC AERIAL DEVICE BUCKET TRUCK

WHEREAS, a bucket truck is an essential tool for the City of Canby Public Works Department for use with tree trimming, street and traffic light maintenance, sign installation and maintenance; and

WHEREAS, Altec Industries, Incorporated manufactures a bucket truck, Model AT 40-G that meets the Public Works Department's needs and specifications as set out in its Request for Proposals due by March 18, 2015; and

WHEREAS, Altec Industries, Incorporated offered the lowest cost bid for its bucket truck, Model AT 40-G; and

WHEREAS, the City of Canby desires to purchase the Altec Bucket Truck for use by its Public Works Department; now therefore

THE CITY OF CANBY, OREGON, ORDAINS AS FOLLOWS:

Section 1. The City Administrator is hereby authorized on behalf of the City of Canby to enter into a contract with Altec Industries to purchase 2016 Altec Bucket Truck for the purchase price of \$124,903.00. A copy of the Formal Proposal from Altec Industries, Incorporated is attached hereto and marked as Exhibit "A" and by this reference incorporated herein.

SUBMITTED to the Canby City Council and read the first time at a regular meeting therefore on April 1, 2015; ordered posted as required by the Canby City Charter and scheduled for second reading on April 15, 2015, after the hour of 7:30 p.m. in the Council Meeting Chambers located at 155 NW 2nd Avenue, Canby, Oregon.


Kimberly Scheafer, MMC
City Recorder

PASSED on second and final reading by the Canby City Council at a regular meeting thereof on the 15th day of April 2015, by the following vote:


YEAS 6

NAYS 0



Brian Hodson
Mayor

ATTEST:



Kimberly Scheafer, MMC
City Recorder



March 9, 2015
Our 86th Year

Ship To:
CITY OF CANBY
182 N HOLLY ST
Canby, OR 97013
US

Bill To:
CITY OF CANBY
182 N HOLLY ST
Canby, OR 97013
United States

Attn: DUSTIN BREESE
Phone: 503-266-0759
Email: BREESED@CI.CANBY.OR.US

Altec Quotation Number: 279894 - 1
Account Manager: David Lee
Technical Sales & Support: John Richard Onders

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	<u>Unit</u>		
1.	ALTEC Model AT40-G telescopic articulating Aerial device with ISO-Boom.	1	
	A. ISO Boom: the inner telescopic fiberglass boom maintains full dielectric integrity even with the fiberglass inner boom fully retracted.		
	B. Hydraulic platform leveling system.		
	C. Hydraulic tool circuit at the platform.		
	D. Emergency lowering valve at the platform.		
	E. Single handle control at the platform with a safety interlock system.		
	F. Two (2) operators and maintenance/parts manuals.		
	G. Working height: 45.6 feet		
	H. Side reach: 29.7 feet		
	I. Low-power fiber-optic control system (FOC-L).		
	J. Continuous rotation		
2.	AT40G Unit Model	1	
3.	Post style pedestal mounting	1	
4.	15 Gallon steel pedestal mounted reservoir With sight gauge.	1	
5.	Single One-Man End-Mounted Platform With 180 Degree Rotator, 24 X 30 X 42. Platform is rated at 400 pounds. Control panel on platform dashboard provides controls for auxillary functions. Includes emergency stop (push-pull) switch and rocker switches, which operate platform leveling, platform rotation, tools, and battery selector (for fiber-optic controls system). Composite fiberglass platform mounting bracket. (AT40G)	1	
6.	Platform Leveling At Lower Controls. AT40-G	1	
7.	Custom Platform Step Inside/outside single step.	1	
8.	254 Platform Cover - foam filled vinyl (24 x 30) for single, one-man, fiberglass platform. Included Altec A logo.	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
9.	4-Function Single Handle Fiber-Optic Controller.	1	
10.	Engine Start/Stop at the upper controls actuated through the Fiber-Optic controls system with Secondary Stowage System (AT40G)	1	
11.	Manual lowering valve located at the boomtip. For use in emergency situations to allow the operator to lower the boom to the ground	1	
12.	H Frame Outriggers, fixed shoe, provides 85.5 inches maximum spread to outer edge of shoes. Includes a control valve for each outrigger, motion alarms to sound during movement, and outrigger interlocks to prevent unit operation until the outriggers have been deployed.	1	
13.	Powder coat unit Altec White.	1	
<u>Unit & Hydraulic Acc.</u>			
14.	HVI-22 Hydraulic Oil (Standard).	17	
15.	Standard Pump For PTO	1	
16.	Hot shift PTO for automatic transmission	1	
17.	Additional return line filter for the hydraulic reservoir	1	
<u>Body</u>			
18.	Altec Body	1	
19.	Steel Body	1	
20.	Low-Side General Service (LGS)	1	
21.	Body Is To Be Built In Accordance With The Following Altec Standard Specifications:	1	
	<ul style="list-style-type: none"> A. Basic Body Fabricated From A40 Grade 100% Zinc Alloy Coated Steel. B. All Doors Are Full, Double Paneled, Self-Sealed With Built-In Drainage For Maximum Weather-Tightness. Hinge Rods Extend Full Length Of Door. C. Heavy-Gauge Welded Steel Frame Construction With Structural Channel Crossmembers And Tread Plate Floor. D. Integrated Door Header Drip Rail At Top For Maximum Weather Protection. E. Fender Panels Are Either Roll Formed Or Have Neoprene Fenderettes Mechanically Fastened. F. Steel Treated For Improved Primer Bond And Rust Resistance. G. Automotive Type Non-Porous Door Seals Mechanically Fastened To The Door Facing. 		
22.	Approximate Body Length (Engineering to Determine Final Length) 112" long. Reverse mount. Unit has outriggers.	1	
	26" from top of floor to top of body.		

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
23.	Custom Body Width 95"	1	
24.	Custom Body Compartment Height 44"	1	
25.	20 Inch Body Compartment Depth	1	
26.	Finish Paint Body Altec White (Applies To Steel And Aluminum)	1	
27.	Undercoat Body	1	
28.	2 Inch x 4 Inch Drop-In Composite Retaining Board At Rear Of Body	1	
29.	Dome Lights (LED) Installed On Horizontal Compartment Tops And On Vertical Compartment Doors, One Per Compartment (Installed At Body Plant)	6	
30.	Stainless Steel T-Handle One-Point Latches With Locks	6	
31.	All Locks Keyed Alike Including Accessories (Preferred Option)	1	
32.	Gas Shock (Gas Spring) Rigid Door Holders On All Vertical Doors	1	
33.	Cable Holders On All Horizontal Doors	1	
34.	Standard Master Body Locking System (Standard Placement Is At Rear. Sidepacks With A Throughshelf/Hotstick Door At Rear, Standard Placement Is At The Front)	6	
35.	One Chock Holder On Each Side of Body With Retaining Lip In Fender Panel (Rear Of Wheel Or Opposite Fuel Fill)	1	
36.	Aluminum Rock Guards Installed Each Front Corner Of Body	1	
37.	Custom 1st Vertical (SS) Compartmentation 32" inch compartment - Three (3) material drawer with thumb latches mounted on 250 pound capacity roller bearing slides. (3"H x 22" W x 16" D). Adjustable dividers installed in each drawer on 6" centers. - Drawer to be mounted 27" up from compartment floor. - Unistrut to be mounted horizontally on side and rear walls - 22" from compartment floor.	1	
38.	Custom 1st Horizontal (SS) Compartmentation 50 inch compartment - One (1) fixed plain shelf midway 10 inches deep. - Compartment bottom will have three (3) fixed lengthwise dividers.	1	
39.	Custom Rear Vertical (SS) Compartmentation Two (2) adjustable shelf with adjustable dividers on six inch center.	1	
40.	Custom 1st Vertical (CS) Compartmentation 32 inch compartment - Unistrut to be mounted horizontally on side and rear walls - 2 inches down from compartment top. - Compartment will be vented to bed area as high as possible.	1	
41.	1st Horizontal (CS) - Vacant Rope lights in this compartment only.	1	
42.	Custom Rear Vertical (CS) Compartmentation 30 inch compartment - Unistrut to be mounted horizontally on side and rear walls - 2 inches down from	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
	compartment top.		
43.	Small Steel Grab Handle Installed At Rear Install streetside and curbside.	2	
44.	Steel U-Shaped Grab Handle Install streetside and curbside.	2	
45.	24" L Steel Tailshelf, Width To Match Body	1	
46.	Steel Cross Storage Located Between Tailshelf Floor And Top Of Chassis Frame Rail, With Drop Down Doors And Keyed Latches On Streetside And Curbside, As Wide As Possible	1	
47.	Step Bumper With CS And SS Gripstrut Steps, Protruding From Rear Face Of Tailshelf, Hanging Below Tailshelf With Kickplate/Back Panel	1	
48.	Vice Bracket Installed On Rear Of Tailshelf Streetside and curbside.	2	
49.	Galvaneal Treadplate Steel Tailshelf In Lieu Of Steel Treadplate	1	
50.	Uni-Strut (B-Line Style) Installed On Curbside Interior Cargo Wall, Mounted As High As Possible 72" long	1	
51.	Uni-Strut (B-Line Style) Installed On Streetside Interior Cargo Wall, Mounted As High As Possible 72" long	1	
52.	Additional Body Option Louver vents between all compartments.	1	
53.	Additional Body Option Conduclt to run front front of body to back, welded to body. All wiring to be run throught conduit.	1	
<u>Body and Chassis Accessories</u>			
54.	Rear Window Guard, With Punched Metal, Perimeter Follows Contour Of Rear Window, Typically Mounted to Body Bulkhead	1	
55.	ICC Underride Protection	1	
56.	Receiver Hitch, 2", Class 3	1	
57.	Set Of D-Rings for Trailer Safety Chain, installed one each side of towing device mount.	1	
58.	Rear Torsion Bar Installed On Chassis Pos 2	1	
59.	Appropriate counterweight added for stability.	1	
60.	Rubber Belted Step Mounted Beneath Side Access Steps (Installed To Extend Approx. 2" Outward) Install streetside and curbside.	2	
61.	Platform Rest, Rigid with Rubber Tube	1	
62.	Boom Rest for a Telescopic Unit	1	
63.	Ratchet Strap For Boom Tie-Down	1	
64.	Plastic Outrigger Pad, 18" x 18" x 1", Black With Handle	2	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
65.	Outrigger Pad Holder, 20" L x 20" W x 3.5" H, Fits 19.5" x 19.5" x 2.25" And Smaller Pads, Bolt-On, Bottom Washout Holes, 3/4" Lip Retainer	1	
66.	Mud Flap Without Altec Logo (Pair)	1	
67.	Wheel Chocks, Rubber with Metal Hairpin Style Handle, 9.75" L X 7.75" W X 5.00" H (Pair)	1	
68.	Slope Indicator Assembly For Machine With Outriggers	1	
69.	Post Style Cone Holder For Installation On A Front Bumper (Holds up to four 15"x15" large cones)	1	
70.	5 LB Fire Extinguisher With Light Duty Bracket, Shipped Loose	1	
71.	Triangular Reflector Kit, Shipped Loose	1	
72.	Soft Vinyl Lanyard Pouch	1	
73.	Vinyl manual pouch for storage of all operator and parts manuals	1	
<u>Electrical Accessories</u>			
74.	Lights and reflectors in accordance with FMVSS #108 lighting package. (LED With Incandescent Reverse Lights)	1	
75.	Custom Strobe Light Install to following strobes. Two (2) Whelen RSA03ZCR in chassis grille. Wired to rocker switch in cab. Two (2) Grote 77353 4" strobes lights recessed into tailshelf. Wired to rocker switch. Wire both sets of strobes to the same rocker switch. Labeled "Warning Lights"	1	
76.	Directional Light Bar, Amber, Super-LED, 47" Long Install in tailshelf.	1	
77.	Cab Mounted Light Bar Whelen #JE8AAA traffic advisor. - Install on roof of cab. - Sealed with silicone to prevent water leaks.	1	
78.	Custom Spot Light Install a Collins FX12 spotlight streetside on rear of compartment tops.	1	
79.	6" Diameter Incandescent Flood Light with Chrome Housing Install on pedestal to light cargo area.	1	
80.	Remote Spot/Flood Light, Night Ray, Incandescent, Par 36 Bulb, 50,000 CP Flood Light / 100,000 CP Spot Light, with Dash Mounted Controls Install on left fender of chassis. Next to F550 logo.	1	
81.	Dual Tone Back-Up With Outrigger Motion Alarm	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
82.	PTO Hour Meter, Analog, with 10,000 Hour Display	1	
83.	Engine Hour Meter, Analog, with 10,000 Hour Display	1	
84.	7-Way Trailer Receptacle (Blade Type) Installed At Rear	1	
85.	Dash panel rocker switches supplied with Ford Chassis, 4 auxiliary switches supplied in up fitting package from Ford	1	
86.	12 Volt Receptacle (Cigarette Lighter Style), Weatherproof - Install streetside first vertical.	1	
87.	Start/Stop/Throttle Module, 12 Volt System Provide a seperate switch and circuit for master. This is to engerize the rest of the switches on the panel.	1	
88.	Install Remote Start/Stop system in Final Assembly. At tailshelf.	1	
89.	Install Outrigger Interlock System	1	
90.	PTO Indicator Light Installed In Cab	1	
91.	Custom Electrical Option Boom stow protection. Limit down pressure once boom in rest in order to protect boom and rest from damage.	1	
92.	Additional Electrical Accessory Outrigger out of stow.	1	
<u>Finishing Details</u>			
93.	Focus Factory Build	1	
94.	Delivery Of Completed Unit	1	
95.	Inbound Freight	1	
96.	Powder Coat Unit Altec White	1	
97.	Custom paint. Top half of body and chassis to be painted Navy blue. Bottom half of chassis body to be gold.	1	
98.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1	
99.	Apply Additional Undercoating from behind the chassis cab to the rear of truck.	1	
100.	Black Undercoating, Applied per Altec Standard	1	
101.	Heavy Duty Cargo Coating, Reflex, Cargo Area Floor and Tailshelf Gator Hyde	1	
102.	English Safety And Instructional Decals	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929



<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
103.	Vehicle Height Placard - Installed In Cab	1	
104.	Dielectric test unit according to ANSI requirements.	1	
105.	Stability test unit according to ANSI requirements.	1	
106.	DOT Certification Required Canby Public Works. Canby OR.	1	
107.	Customer Inspection Required	1	
108.	Placard, HVI-22 Hydraulic Oil	1	
109.	FA Unit Designator - AT40G Aerial Device	1	
110.	Additional Finishing Detail RED Dot Heater (Manufacturer is RED Dot): Flush mounted, 16,000 BTU, 3.3 Amp, 12 Volt with the use of 5/8" fittings. <ul style="list-style-type: none">• Installed In 1" curb-side vertical compartment.• Uses engine hot water for heat source.• Includes a fan on/off switch in cab.• Heater will be installed in front compartment.• Heater hose to be blue Goodyear Hi-Miler J20R3 D3 HT Punched metal drying rack.	1	
<u>Chassis</u>			
111.	Chassis	1	
112.	Altec Supplied Chassis	1	
113.	2016 Model Year	1	
114.	Ford F550	1	
115.	4x2	1	
116.	60 Clear CA (Round To Next Whole Number)	1	
117.	Extended Cab (Larger Cab With Half-Length Rear Doors Or No Rear Doors)	1	
118.	Chassis Color - White	1	
119.	Ford Gas 6.8L	1	
120.	Ford Torqshift 5 Speed Automatic Transmission (w/PTO Provision)	1	
121.	GVWR 19,000 LBs	1	
122.	6,500 LBs Front Axle Rating	1	
123.	14,706 LBs Rear Axle Rating	1	
124.	225/70R19.5 Front Tire	1	
125.	225/70R19.5 Rear Tire	1	

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You


UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>	<u>Price</u>
126.	Hydraulic Brakes	1	
127.	Ford E/F250-550 Single Horizontal Right Side Exhaust	1	
128.	No Idle Engine Shut-Down Required	1	
129.	40 Gallon Fuel Tank (Behind Rear Axle)	1	
130.	Air Conditioning	1	
131.	AM/FM Radio	1	
132.	Cruise Control	1	
133.	Power Door Locks	1	
134.	Power Windows	1	
135.	Trailer Brake Controller (Factory Installed)	1	
136.	Other Exterior Cab Options heated power mirrors.	1	
137.	Vinyl Split Bench Seat	1	
<u>Additional Pricing</u>			
138.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1	
<u>Miscellaneous</u>			
139.	Ext Warranty Travel, Labor, Matl., Expense (Day 91-730) Buckets Less Than 46 FT (AT237, AT30-GV, AT-G, AO,TA, L Series, LM)	1	

Unit / Body / Chassis Total	124,903.00
FET Total	0.00
Total	124,903.00

Altec Industries, Inc.

BY



John Richard Onders

Notes:

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

- 1 Altec Standard Warranty:
- One (1) year parts warranty.
 - One (1) year labor warranty.
 - Ninety (90) days warranty for travel charges.
- Warranty on structural integrity of the following major components is to be warranted for so long as the initial purchaser owns the product: Booms, boom articulation links, hydraulic cylinder structures, outrigger weldments, pedestals, subbases and turntables.
- Bidder is to supply a self-directed, computer based training (CBT) program. This program will provide basic instruction in the safe operation of this aerial device. This program will also include and explain ANSI and OSHA requirements related to the proper use and operation of this unit.
- Altec offers its standard limited warranty with the Altec supplied components which make up the Altec Unit and its installation, but expressly disclaims any and all warranties, liabilities, and responsibilities, including any implied warranties of fitness for a particular purpose and merchantability, for any customer supplied parts
- Altec designs and manufactures to applicable Federal Motor Vehicle Safety and DOT standards
- 2 Altec takes pride in offering solutions that provide a safer work environment for our customers. In an effort to focus on safety, we would like to ensure that the following items are offered to you as part of the attached quotation package:
- Outrigger pads (When Applicable)
 - Fall Protection System
 - Fire extinguisher/DOT kit
 - Platform Liner (When Applicable)
 - Back up alarm
 - Wheel Chocks
- The aforementioned equipment is traditionally offered in our new equipment quotations, unless requested otherwise by the customer. If you find that any of these items have not been listed as priced options in the body of your quotation and are required by your company, we would encourage you to contact your Altec Account Manager and have an updated quotation developed for you. These options must be listed as individual options in the body of the quotation for them to be supplied by Altec.
- 3 Unless otherwise noted, all measurements used in this quote are based on a 40 inch (1016mm) chassis frame height and standard cab height for standard configurations.
- 4 F.O.B. - #FOB_TERMS#
- 5 Changes made to this order may affect whether or not this vehicle is subject to F.E.T. A review will be made at the time of invoicing and any applicable F.E.T. will be added to the invoice amount.
- 6 Price does not reflect any local, state or Federal Excise Taxes (F.E.T). The quote also does not reflect any local title or licensing fees. All appropriate taxes will be added to the final price in accordance with regulations in effect at time of invoicing.
- 7 Interest charge of 1/2% per month to be added for late payment.
- 8 Delivery: 270-300 ARO days after receipt of order PROVIDING:

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You

UTILITY EQUIPMENT AND BODIES SINCE 1929

- A. Order is received within 14 days from the date of the quote. If initial timeframe expires, please contact your Altec representative for an updated delivery commitment.
- B. Chassis is received a minimum of sixty (60) days before scheduled delivery.
- C. Customer approval drawings are returned by requested date.
- D. Customer supplied accessories are received by date necessary for compliance with scheduled delivery.
- E. Customer expectations are accurately captured prior to releasing the order. Unexpected additions or changes made at a customer inspection will delay the delivery of the vehicle.

Altec reserves the right to change suppliers in order to meet customer delivery requirements, unless specifically identified, by the customer, during the quote and or ordering process.

- 9 Trade-in offer is contingent upon equipment being maintained to DOT (Department of Transportation) operating and safety standards. This will include, but not limited to tires, lights, brakes, glass, etc. If a trade-in is not maintained to DOT standards, additional transportation expenses will apply and could be invoiced separately.

All equipment, i.e., jibs, winches, pintle hooks, trailer connectors, etc., are to remain with the vehicle unless otherwise agreed upon in writing by both parties. Altec Industries reserves the right to re-negotiate its trade-in offer if these conditions are not met.

Customer may exercise the option to rescind this agreement in writing within sixty (60) days after receipt of purchase order. After that time Altec Industries will expect receipt of trade-in vehicle upon delivery of new equipment as part of the terms of the purchase order.

Titles for trade-in equipment should be given to the appropriate Altec Sales associate or forwarded to Altec Nuevo at address 1730 Vanderbilt Road, Birmingham, AL 35234.

- 10 This quotation is valid until MAY 08, 2015. After this date, please contact Altec Industries, Inc. for a possible extension.

- 11 After the initial warranty period, Altec Industries, Inc. offers mobile service units, in-shop service and same day parts shipments on most parts from service locations nationwide at an additional competitive labor and parts rate. Call 877-GO-ALTEC for all of your Parts and Service needs.

- 12 Please email Altec Capital at finance@altec.com or call 888-408-8148 for a lease quote today.

- 13 Please direct all questions to David Lee at (270) 360-0600