

DEPARTMENT OF ENVIRONMENTAL QUALITY

DIVISION 244

OREGON FEDERAL AND STATE HAZARDOUS AIR POLLUTANT PROGRAM

340-244-9070

Emission Control Device Requirements

(1) Each emission control device used to comply with this rule must meet 99.0 percent or more removal efficiency for particulate matter as measured by ~~DEQ~~[EPA](#) Method 5 or an equivalent method approved by DEQ.

(2) Emission control device requirements:

(a) A CAGM must obtain DEQ approval of the design of all emission control devices before installation, as provided in this rule.

(b) A CAGM must submit a Notice of Intent to Construct as required by OAR 340-210-0205 through 340-210-0250 no later than 15 days before the date installation begins. If DEQ does not deny or approve the Notice of Intent to Construct within 10 days after receiving the Notice, the Notice will be deemed to be approved.

(c) Emission control devices may control emissions from more than one glass-making furnace.

(d) Each emission control device must be equipped with the following monitoring equipment:

(A) An inlet temperature monitoring device;

(B) A differential pressure monitoring device if the emission control device is a baghouse; and

(C) Any other monitoring device or devices specified in DEQ's approval of the Notice of Intent to Construct.

(e) Each emission control device must be equipped with inlet ducting that provides the following:

(A) Sufficient cooling of exhaust gases to no more than the maximum design inlet temperature under worst-case conditions; and

(B) Provision for inlet emissions testing, including sufficient duct diameter, sample ports, undisturbed flow conditions, and access for testing.

(f) Each emission control device must be equipped with outlet ducting that provides for outlet emissions testing, including sufficient duct diameter, sample ports, undisturbed flow conditions, and access for testing.

(g) After commencing operation of any emission control device, the CAGM must monitor the emission control device as required by OAR 340-244-9080.

(h) A CAGM must perform the following source testing on at least one emission control device. Source testing done under OAR 340-244-9040(2) may be used in whole or in part to comply with this requirement.

(A) Within 60 days of commencing operation of the emission control devices, test control device inlet and outlet for particulate matter using DEQ Method 5 or equivalent method;

(B) The emission control device to be tested must be approved by DEQ;

(C) A source test plan must be submitted at least 30 days before conducting the source test; and

(D) The source test plan must be approved by DEQ before conducting the source test.

Stat. Auth.: ORS 468.020, 468A.025, & 468A.040

Stats. Implemented: ORS 468A.025, & 468A.040