



OAR 340-035-0030

Table 2 In-Use Road Vehicle Standards Stationary Test

| Model Year | Maximum Noise Level (dBA) | Minimum Distance from Vehicle to Measurement Point |
|---|---------------------------|--|
| All Vehicles Described in ORS 481.205(2) | | |
| Before 1976 | 94 | 25 feet (7.6 meters) |
| 1976 and after | 91 | 25 feet (7.6 meters) |
| All Other Trucks in Excess of 8,000 pounds (3629 kg.) GVRW | | |
| Before 1976 | 94 | 25 feet (7.6 meters) |
| 1976-1981 | 91 | 25 feet (7.6 meters) |
| After 1981 | 88 | 25 feet (7.6 meters) |
| Motorcycles | | |
| 1975 and Before | 102 | 20 inches (1/2 meter) |
| After 1975 | 99 | 20 inches (1/2 meter) |
| Front-engine Automobiles, Light Trucks, All Other Front-engine Road Vehicles | | |
| All | 95 | 20 inches (1/2 meter) |
| Rear-engine Automobiles, Light Trucks and All Other Front-engine Road Vehicles | | |
| All | 95 | 20 inches (1/2 meter) |
| Buses as Defined Under ORS 481.030 | | |
| Before 1976 | 94 | 25 feet (7.6 meters) |
| 1976 and After | 91 | 25 feet (7.6 meters) |