




INDUSTRIAL HYGIENE
ENVIRONMENTAL ENGINEERING
CONSTRUCTION SERVICES

Offices Nationwide



EIGHTH QUARTERLY GROUND WATER MONITORING REPORT

Delco Company (formerly Flying J) 17873 SE McLoughlin Boulevard Milwaukie, Oregon 97267

> Project Number 38-000002 (formerly 16122)

Prepared for:
Devinder Dhillon
14 Longleaf Drive
Hamilton Square, New Jersey

DEPT OF ENVIRONMENTAL QUALITY RECEIVED

DEC 9 1996

NORTHWEST REGION

November 8, 1996

Prepared by: Jeff Jackman

Northwest Envirocon, Inc. 7410 Delaware Lane Vancouver, Washington 98664 (360) 699-4015

TABLE OF CONTENTS

1.0	INTRODUCTION	3
	1.1. Objective	
	1.2. Background	
2.0	GROUND WATER MONITORING ACTIVITIES	5
	2.1. Ground Water Sampling Methods	5
	2.2. Ground Water Analysis and Results	6
3.0	FREE PRODUCT RECOVERY	
4.0	CONCLUSIONS AND RECOMMENDATIONS	7
5.0	LIMITATIONS	
6.0	APPENDICES.	9

1.0 INTRODUCTION

This report is to summarize the eighth quarterly ground water sampling event that took place on October 29, 1996 at the Milwaukie Fuel Stop/Delco facility (formerly Flying J) in Milwaukie, Oregon. This site is located at 17873 McLoughlin Boulevard, as shown in Appendix A of this report. On October 29, 1996; ground water was sampled from each of the twelve (12) monitoring wells on the site. Analytical results indicated that the benzene concentration exceeds the Oregon Cleanup Level of 5 parts per billion (ppb) in wells MW-1, MW-2, MW-4, MW-5, and MW-7. None of the wells exceeded the allowable limits of 700 ppb ethylbenzene, 10,000 ppb total xylenes, or 1,000 ppb toluene.

No free product was observed in any of the wells during this sampling event.

1.1 Objective

The purpose of this investigation was to monitor the environmental impact of a petroleum hydrocarbon plume to the ground water at the Delco (formerly Flying J) gasoline station in Milwaukie, Oregon.

1.2 Background

In May of 1993, Delta Environmental of Bellevue, Washington conducted a Phase I Environmental Assessment of the Flying J (now Delco) gasoline station in Milwaukie, Oregon. Conclusions based on the results of the Phase I indicated the likelihood that the facility may have had an unauthorized release, and a Phase II preliminary site characterization was initiated. Geotech Exploration drilled five soil borings in prearranged locations within the property's boundaries. The borings did not penetrate the soil/groundwater interface. Soil samples were collected from each of the borings and analyzed for benzene, toluene, ethylbenzene and xylenes (BTEX), total petroleum hydrocarbons (TPH) and total petroleum hydrocarbons as gasoline (TPH-G). Concentrations of BTEX and TPH were found in the soil samples in levels high enough to warrant additional drilling on the site. All five borings were subsequently abandoned with concrete after the investigation was concluded.

In June of 1993, Geotech Explorations and Delta Environmental drilled six monitoring wells on the site to evaluate the potential environmental impact to ground water. According to the Delta Environmental Phase III report, the wells on the site are constructed of flush-jointed, 2-inch diameter, schedule 40 PVC pipe, fitted with 10-foot long, 0.020-inch factory slotted well screens. In each well, the screen was set at a depth which intersected the groundwater surface observed at the time of the drilling, and was surrounded by a washed silica sand filter pack to a level at least one foot above the top of the screened interval. The remaining borehole was filled with bentonite, and the well was completed with a concrete seal and a flush-mounted locking steel protective well box at the ground surface.

The results of the sampling conducted in June 1993 indicated that soils from borings MW-1 through MW-5 contained concentrations of benzene, toluene, ethylbenzene and xylenes (BTEX), total petroleum hydrocarbons (TPH) and total petroleum hydrocarbons as gasoline (TPH-G). Benzene and TPH were above Oregon Cleanup Levels in borings MW-1 through MW-5. Ground water was sampled and analyzed from each of the six wells for BTEX, TPH, and TPH-G. Laboratory analysis of the water samples obtained indicated that MW-1 through MW-5 contained concentrations of benzene and TPH which exceeded Oregon cleanup levels. MW-6 however, showed concentrations of benzene and TPH below Oregon cleanup requirements.

Since the completion of Delta Environmental Phase III in June 1993, the ground water on this site had not been sampled until July 1994 when Northwest Envirocon, Inc. was retained by Mr. Devinder Dhillon to sample the ground water from each of the six monitoring wells previously drilled by Geotech Explorations. This July, 1994 sampling event served as the first quarterly monitoring. Since that time, Northwest Envirocon has conducted second, third, fourth, fifth, and sixth quarter ground water monitoring at this site.

On January 27,1995 three (3) new monitoring wells were installed by Tankliners. These wells were designated MW-7, MW-8, and MW-9. MW-7 and MW-8 are four inches in diameter and were installed to accommodate a groundwater treatment system. MW-9 is a two-inch diameter well to be used for ground water monitoring, and was installed hydrologically up-gradient as recommended by the Oregon Department of Environmental Quality. Please refer to the ground water contour map in Appendix B for well locations.

MW-7 and MW-8 are constructed of flush-jointed, 4-inch diameter, schedule 40 PVC pipe, fitted with 15-foot long, 0.020-inch factory slotted well screens. In each well, the screen was set at a depth which intersected the groundwater surface observed at the time of the drilling, and was surrounded by a washed silica sand filter pack to a level at least one foot above the top of the screened interval. The remaining borehole was filled with bentonite, and the well was completed with a concrete seal and a flush-mounted locking steel protective well box at the ground surface. MW-9 is of the same construction except that the diameter is 2" and the screened interval is 10 feet.

On February 20, 1995 (after the third quarter monitoring) MW-3 was decommissioned by Geotech Explorations due to repairs to the asphalt in the vicinity of the well.

The soil which had been stockpiled on the site from earlier tank removal activities was removed from the site and disposed at Roosevelt Regional Landfill in Roosevelt, Washington on March 22, 1995.

A ground water remediation system was installed on site and has been operating since September 6, 1995. The system was manufactured by Environmental Products Northwest and is operating under National Pollutant Discharge Elimination System (NPDES) Waste Discharge Permit #1500A. A copy of this permit, as well as specifications for the treatment system are included in Appendix F.

On August 12,1996 four (4) new monitoring wells were installed by Environmental West Exploration, Inc. These wells were designated MW-10, MW-11, MW-12, and MW-13. All of these are two-inch diameter wells. Initial sampling was conducted on September 17 and September 18, 1996 after development of the wells had been completed. These samples were analyzed for Total Petroleum Hydrocarbons as gasoline (EPA Method TPH-G) and for Benzene, Toluene, Ethylbenzene, and Xylenes (EPA Method 602) by On-Site Environmental, Inc. of Redmond, Washington. No contamination was detected by the laboratory in any of these initial samples. Please refer to the ground water contour map in Appendix B for well locations.

MW-10, MW-11, MW-12, and MW-13 are constructed of flush-jointed, 2-inch diameter, schedule 40 PVC pipe, fitted with 5-foot long, 0.010-inch factory slotted well screens. In each well, the screen was set at a depth which intersected the groundwater surface observed at the time of the drilling, and was surrounded by a washed silica sand filter pack to a level at least one foot above the top of the screened interval. The remaining borehole was filled with bentonite, and the well was completed with a concrete seal and a flush-mounted locking steel protective well box at the ground surface. Installation documents for these wells have been included in the Appendices.

Discharge samples have been collected as per requirements outlined in the NPDES Permit. No BTEX contamination was detected in any of these discharge samples. A table and laboratory records pertaining to these samples are included in Appendix E.

2.0 GROUND WATER MONITORING ACTIVITIES

2.1. Groundwater Sampling Methods

To ensure representative ground water samples were obtained, on October 29, 1996 Northwest Envirocon field technicians purged a minimum of three well volumes from each of the monitoring wells. Voss® disposable bailers were used for the purging of all wells except MW-7 and MW-8. Valves installed as part of the treatment system were used to purge wells MW-7 and MW-8. The purged water from each well was collected and is stored in 55-gallon drums on the site for future disposal. Static water level measurements were taken using a Slope® Water Level Indicator accurate to 0.01 feet. Since the intake pumps and associated control equipment for the abovementioned treatment system are located in wells MW-7 and MW-8, it is not possible to obtain an accurate measurement of the static water level in these wells with the Slope® Water Level Indicator. Therefore, ground water gradient calculations were performed without measurements from these two wells.

The twelve wells on site are fast recharging wells; and after purging, each well was allowed to recharge to at least 85 percent of its original volume prior to sampling. Sampling methodology is as follows:

MW-1, MW-2, MW-4, MW-5, MW-6, MW-9, MW-10, MW-11, MW-12 and MW-13: The ground water was sampled using a new, pre-wrapped Voss® single sample disposable bailer and a new set of latex gloves for each well. Nylon twine was replaced between each sampling event to decrease the risk of cross-contamination.

MW-7 and MW-8: Ground water samples were collected through permanently installed valves in the treatment system.

In the case of all twelve wells, water was discharged into two 40 milliliter glass VOA vials which were supplied by Wy'East Laboratory. The samples were collected with no headspace in the vials. The water sample vials were labeled and stored in a cooler with ice packs and transported to Wy'East Laboratory in Portland with the appropriate chain-of-custody. All twelve samples were analyzed using EPA method 8020 (BTEX). Copies of the chain-of-custody and laboratory results are contained in Appendix C.

Static water level measurements were recorded for wells MW-1, MW-2, MW-4, MW-5, MW-6, MW-9, MW-10, MW-11, MW-12 and MW-13 with a Slope® Water Level Indicator. The levels obtained from each well are indicated on the following page.

Groundwater Elevations

Monitoring Well	Depth to ground water	Elevation of Well
MW-1	5.82 feet	99.67 feet
MW-2	5.00 feet	98.79 feet
MW-4	5.55 feet	99.30 feet
MW-5	6.95 feet	100.66 feet
MW-6	6.47 feet	100.29 feet
MW-9	5.66 feet	99.72 feet
MW-10	4.94 feet	98.77 feet
MW-11	6.37 feet	99.98 feet
MW-12	6.68 feet	100.54 feet
MW-13	6.29 feet	100.11 feet

Based on the ground water measurements, the ground water flow gradient at the time of this sampling event sloped to the northwest. A groundwater contour map is contained in the Appendices.

2.2 Ground Water Analysis and Results

Northwest Envirocon conducted the eighth quarterly ground water sampling event on October 29, 1996. A total of twenty-four 40-milliliter VOA vials (two from each well) were analyzed by Wy'East Laboratory for BTEX. The results were compared to the Oregon UST Cleanup Levels [340-122-242(4)]. Laboratory analysis revealed that five of the twelve monitoring wells exceeded the Oregon cleanup level of 5 parts per billion (ppb) benzene. None of the wells exceeded the cleanup levels for toluene, ethylbenzene, or xylenes. The following charts show the laboratory results relative to Oregon Cleanup levels.

Oregon Cleanup Levels [340-122-242(4)]

dqq 000,01	dqq 007	dqq 000,1	qdd c
Xylenes	Ethylbenzene	Toluene	Benzene

Laboratory Analytical Results for BTEX

ND	ND ND	D	13 EI-WM
ND	ND (D	MW-12
ND	ND	D	I II-WM
ND	UN	D	1 01-WM
ND	ON	D	1 6-MW
ND	an I	D	1 8-WM
867	qdd g	86	Z L-MW
ND	ND (D	1 9-WM
320	7	05	S-WM
067	dqq 21	06	t-WM
24 H	ND (d t	Z-WM
731	qdd ç	18	Z I-MW

A copy of the laboratory results and chain-of-custody can be found in Appendix C.

3.0 FREE PRODUCT RECOVERY

No free product was observed during this eighth quarterly ground water sampling.

4.0 CONCLUSIONS AND RECOMMENDATIONS

The results of this sampling event indicate an overall decrease in BTEX concentration in MW-1, MW-2, MW-4, MW-7, and MW-8, and a slight overall increase in MW-5 since the seventh quarterly sampling event on April 26, 1996. No BTEX constituents were detected in MW-6, MW-8, MW-9, MW-10, MW-11, MW-12, or MW-13. Benzene was the only BTEX constituent in excess of Oregon cleanup levels. Northwest Envirocon recommends the continued monitoring of the groundwater at this site as well as regular inspection and maintenance of the treatment system.

* Exceeds Oregon Cleanup Levels

5.0 LIMITATIONS

This assessment has been performed in accordance with generally accepted environmental practices and procedures, as of the date of the report. All services have been performed employing that degree of care and skill ordinarily exercised under similar circumstances by reputable environmental technologists practicing in this, or similar localities. No other warranty or guarantee, expressed or implied, is made or offered.

The conclusions and recommendations stated in this report are based upon observations made by employees of Northwest Envirocon, Inc. and also upon information provided by others. We have no reason to suspect or believe that the information provided is inaccurate. However, we cannot be held responsible for the accuracy of the information provided to us by others.

Jeff Jackman

Senior Environmental Assessor

Dennis Hudson


President

6.0 APPENDICES

	A STATE OF THE PARTY OF THE PAR		-	-
A	· Int	ograp	hic	Man
11	10	rogiup	inc	Triup

- B Ground Water Contour Map
- Laboratory Results and Chain of Custody for Eighth Quarterly Sampling Event
- D Ground Water Elevation Summary
- Daily, Weekly, and Monthly Discharge Monitoring Records and Associated Laboratory Results and Chain of Custody
- F Treatment System Specifications and Permit
- Well Installation Documents for MW-10, MW-11, MW-12, and MW-13

Appendix A





Northwest Environm, Inc. Environmental Consulting


USGS 1:24,000 Topographic Map Gladstone Quadrangle

JOB NUMBER 38-00002

DATE

November 8, 1996

Appendix B



Appendix C



Wy'East Environmental Sciences, Inc.

LABORATORY REPORT

Northwest Envirocon 7410 Deleware Lane Vancouver WA 98664

PROJECT NAME/SITE: PROJECT NUMBER:

Delco 38-000002 REPORT NUMBER: REPORT DATE:

17693 10-30-96

EXTRACTION DATE:

10-29-96

PAGES:

1 of 1

EPA 8020

Analyte: BTEX for water (Benzene, Toluene, Ethylbenzene, Xylenes)

Field ID	Lah ID	Identific	cation & Qua	g/I. (pph)	Surrogate	
		Benzene	Toluene	Ethyl-	Xylenes	Recovery (%)
				Benzene	-	
MW-1	29156	231	5	18	15	106
MW-2	29157	54	ND	ND	ND	96
MW-4	29158	490	15	123	442	100
MW-5	29159	350	2	23	49	98
MW-6	29160	ND	ND	ND	ND	89
MW-7	29161	298	5	16	55	92
MW-8	29162	ND	ND	ND	ND	97
MW-9	29163	ND	ND	ND	ND	86
MW-10	29164	ND	ND	ND	ND	90
MW-11	29165	ND	ND	ND	ND	90
MW-12	29166	ND	ND	ND	ND	84
MW-13	29167	ND	ND	ND	ND	82
BLANK	_	ND	ND	ND	ND	₽ ' '
Quantification Limits	-	2	2	2	2	-

Surrogate is p-Bromofluorobenzene

ND = Not Detected (below reporting limit or detection limit)

Report	Number:	
--------	---------	--

Environmental Sciences, Inc.

Research, Laboratory, and Consulting Services

CHAIN OF CUSTODY	2415 SF 11th	Ave • Portland Oregon 97214	• (503) 231-9320 • FAX (503) 231-934
CHAIN OF CUSTOD!	2413 SE 11til	Ave. Tornand, Oregon 97214	(303) 231-9320 • FAA (303) 231-93-

PROJECT #	PROJECTI	VAME / SITE	S	STATE OR	PURCHASE OF	RDER# 17628
38-000002						園 か 以 と む
COMPANY	REPORT A	TTENTION		PHONE NUMBER 360 699 4015	FAX NUMBER 360 G99	C223
SAMPLES COLLECTED BY	DATE COLL	ECTED	7	TIME COLLECTED	SAMPLES CHIL	LED TO 4° C?
SAMPLES COLLECTED BY	DATE COLL	al.		3:00 pm to 4:00 pm	yes	
PRESERVATIVE USED? (HCl, etc.)					/	
FIELD ID	MEDIA	CONTAINER	VOLUME ET	C. ANALYSIS R	EQUIRED	LAB ID
MW-1	Water	VoA	2×40 ml	BTEX		29156
MW-2		1				29157
MW-4						29158
MW.5				\ .		29159
NW-6						29160
MW-7						29161
MW-8						29162
MW-9						29163
MW-10					9	29164
MW-11						29165
MW-12						29166
MW-13		1	1			24167
1						
RELINQUISHED BY		10/29/96 DA	TE/TIME I	RECEIVED BY	rung	DATE/TIME - 10-29-46 4
RELINQUISHED BY		DA	TE/TIME I	RECEIVED BY LAB	73	DATE / TIME
REMARKS				SHIPPED BY		

Appendix D

Ground Water Elevation Summary

October 29, 1996

Well#	Top of riser elevation	measured depth to ground water (in feet)	Product layer	Ground water elevation
MW-1	99.67	5.82	none	93.85
MW-2	98.79	5.00	none	93.79
MW-4	99.30	5.55	none	93.75
MW-5	100.66	6.95	none	93.71
MW-6	100.29	6.47	none	93.82
MW-9	99.72	5.66	none	94.06
MW-10	98.77	4.94	none	93.83
MW-11	99.98	6.37	none	93.61
MW-12	100.54	6.68	none	93.86
MW-13	100.11	6.29	none	93.82

Appendix E

DISCHARGE MONITORING CHART

Date/Time	BTEX	TPH-G	Ph	Flow (gal)
9-6-95/12:50	Not Sampled	Not Detected	7.99	12,600
9-7-95/12:55	Not Sampled	Not Detected	8.04	17,770
9-8-95/12:51	Not Sampled	Not Detected	8.03	22,890
9-9-95/12:40	Not Sampled	Not Detected	8.13	28,000
9-10-95/12:42	Not Sampled	Not Detected	8.35	33,850
9-20-95/12:19	Not Detected	Not Detected	8.26	87,710
9-27-95/11:41	Not Detected	Not Detected	8.23	178,570
10-5-95/13:14	Not Detected	Not Detected	8.63	221,850
10-11-95/14:19	Not Detected	Not Detected	8.55	257,810
10-19-95/13:46	Not Detected	Not Detected	8.50	294,410
10-26-95/11:39	Not Detected	Not Detected	8.50	342,545
11-10-95/13:17	Not Detected	Not Detected	8.03	409,211
11-17-95/14:22	Not Detected	Not Detected	8.40	443,550
11-24-95/11:19	Not Detected	Not Detected	8.50	476,401
11-30-95/10:51	Not Detected	Not Detected	8.36	518,990
12-08-95/11:51	Not Detected	Not Detected	8.33	577,010
12-14-95/13:53	Not Detected	Not Detected	7.34	589,720
12-22-95/11:48	Not Detected	Not Detected	6.90	626,341
12-29-95/11:20	Not Detected	Not Detected	8.38	670,450
01-05-96/11:03	Not Detected	Not Detected	8.42	711,683
01-12-96/16:15	Not Detected	Not Detected	8.40	746,880
01-19-96/17:17	Not Detected	Not Detected	8.43	784,400
01-26-96/15:37	Not Detected	Not Detected	8.29	821,511

DISCHARGE MONITORING CHART (continued)

Date/Time	BTEX	TPH-G	<u>Ph</u>	Flow (gal)
02-06-96/09:56	Not Detected	Not Detected	8.41	878,570
02-12-96/14:27	Not Detected	Not Detected	8.40	910,340
02-19-96/11:36	Not Detected	Not Detected	8.45	944,980
02-26-96/10:35	Not Detected	Not Detected	8.30	979,180
03-04-96/10:35	Not Detected	Not Detected	8.39	1,014,950
03-11-96/13:15	Not Detected	Not Detected	8.34	1,050,270
03-19-96/13:00	Not Detected	Not Detected	8.46	1,092,040
03-25-96/13:30	Not Detected	Not Detected	8.34	1,113,980
04-01-96/12:05	Not Detected	Not Detected	8.40	1,143,750
05-13-96/15:23	Not Detected	Not Detected	8.32	1,310,840
06-03/11:00	2ppb benzene 5ppb toluene ND ethylbenzene ND xylenes	Not Detected	8.33	1,447,230
07-03/13:55	Not Detected	Not Detected	8.36	1,669,080
08-06/12:08	Not Detected	Not Detected	8.37	1,831,380
09-19/09:30	Not Detected	Not Detected	8.48	1,981,210
10-18/13:00	Not Detected	Not Detected	7.71	2,146,600

LABORATORY REPORT

Northwest Envirocon 7410 Deleware Lane Vancouver, WA 98664 JECEIVED JUN - 6 1996 By_____

PROJECT NAME/SITE:

Delco

REPORT NUMBER:

16755

PROJECT NUMBER:

38-000002

REPORT DATE:

6-4-96

EXTRACTION DATE:

6-3-96

PAGES:

1 of 1

EPA 8020

Analyte: BTEX for water (Benzene, Toluene, Ethylbenzene, Xylenes)

Field ID	Lab ID	Identific	cation & Qua	Surrogate		
		Benzene	Toluene	Ethyl-	Xylenes	Recovery (%)
				Benzene		
DSC0603	26195	2	5	ND	ND	96
BLANK	-	ND	ND	ND	ND	-
Quantification Limits	-	2	2	2	2	-

Surrogate is p-Bromofluorobenzene

ND = Not Detected (below reporting limit or detection limit)

TPH-G modified for water

Analyte: Total Petroleum Hydrocarbon Quantification

Field ID	Lab ID	Matrix	μg/L (ppb)
DSC0603	26195	WATER	ND
BLANK	_	-	ND
Detection Limit	-	-	125

ND = Not Detected (below reporting limit or detection limit)

EPA 150.1 pH

Direction pin			
Field ID	Lab ID	рН	
DSC0603	26195	8.33	

Wy East

Environmental Sciences, Inc.

CHAIN OF CUST	ГО	CUSTO	DY
---------------	----	-------	----

In my work me				
	EC		VE	
	JUN	- 6	1996	

Ву

Report Number: ______16755

Research, Laboratory, and Consulting Services

2415 SE 11th Ave. • Portland, Oregon 97214 • (503) 231-9320 • FAX (503) 231-9344

PROJECT#	PROJECT N	INME / SITE	T	CTA	TE	D//D0//40= 0====	
				STA		PURCHASE ORDER	.#
38-000 <i>0</i> 02	Delco				()P	96480 DO 15	552KC
COMPANY	REPORT AT	TEŅTION			NE NUMBER	96480 DO 15 FAX NUMBER	_
HW Envirocon	Jeff 1	ackman ECTED		150	3) 230-0702	(360)699-5 SAMPLES CHILLED	-223
SAMPLES COLLECTED BY	DATE COLL	ECTED		TIME	COLLECTED	SAMPLES CHILLED	TO 4° C2
K. Copley	6-3-	96		/	(9: 80am	O, IIII EEO O, IIIEEED	104 0.
K. Cooley RESERVATIVE USED? (HCI, etc.)					y occup		
(100, 000)							
FIELD ID	MEDIA	CONTAINER	VOLUME ET	TC	ANALYCIC DEOL	Inrh	
FIELD ID	DATE				ANALYSIS REQU	THE RESERVE OF THE PROPERTY OF THE PARTY OF	LAB ID
DSC0603	way ten	VOA	40 ml	-	PH, TPH-G, RTE	- / -	26195
	re			7	/ / / · · · · / · · · · / · · · · · · ·		
							٠.
	=						
	Э						
	12						
	la la						

	_						
. S. A. San							
1							
RELINQUISHED BY	//	D47	E/TIME	REC	EIVED BY		DATE / TIME
THE	_	6-3-96 1	1/200	NLO	DEIVED BT		DATE / TIME
REMNQUISHED BY	7	7/1	TE/TIME	DEC	CEIVED BY LAB , i		DATE / T045
NEED BY		DAT	L/ ITIVIE	KEU		1/2/2/	DATE / TIME
DEMARKS				CLU	Cil. Chan	0/3/76/	1:20 AM
REMARKS				SHIF	PPED BY	1	
			1				

Wy East will return white copy to client with laboratory report and keep yellow copy for files. Client keeps pink copy.

LABORATORY REPORT

Northwest Envirocon 7410 Deleware Lane Vancouver WA 98664 JUL 1 0 1996

PROJECT NAME/SITE:

Delco

REPORT NUMBER:

16947

PROJECT NUMBER: EXTRACTION DATE:

38-000002 7-3-96 REPORT DATE: PAGES:

7-8-96 1 of 1

EPA 8020

Analyte: BTEX for water (Benzene, Toluene, Ethylbenzene, Xylenes)

Field ID	Lab ID	Identific	cation & Qua	ıg/L (ppb)	Surrogate	
		Benzene	Toluene	Ethyl-	Xylenes	Recovery (%)
		= n		Benzene	1 850	
PSC 0703	26815	ND	ND	ND	ND	113
BLANK	-	ND	ND	ND	ND	-
Quantification Limits	_	2	2	2	2	_

Surrogate is p-Bromofluorobenzene

ND = Not Detected (below reporting limit or detection limit)

TPH-G modified for water

Analyte: Total Petroleum Hydrocarbon Quantification

Field ID	Lab ID	Matrix	μg/L (ppb)
PSC 0703	26815	WATER	ND
BLANK	- <u>-</u>	-	ND
Detection Limit	=	, =	125

ND = Not Detected (below reporting limit or detection limit)

EPA 150.1 pH

Field ID	Lab ID	pН
PSC 0703	26815	8.36

EDECOM	HOUSEHOLD			1000	Name and Address of the Owner, where the Owner, which is the Own
	1	6	1 4	1	-
1	4	0	3		1

Report Number:	
-----------------------	--

Environmental Sciences, Inc.

JUL 1 0 1996

Research, Laboratory, and Consulting Services

CHAIN OF CUSTODY

2415 SE 11th Ave. • Portland, Oregon 97214 • (503) 231-9320 • FAX (503) 231-9344

PROJECT # SOCOOO COMPANY NW SAMPLES COLLECTED BY PRESERVATIVE USED? (HCI, etc.)	PROJECT N REPORT AT Self DATE COLL	TENTION ECJED		STATE CR PHONE NUMBER 360 699 4015 TIME COLLECTED /:55 p.m	PURCHASE ORDER P96480001 SI FAX NUMBER 360 679 SZ SAMFLES CHILLED	223
FIELD ID	MEDIA	CONTAINER	VOLUME ET	TC. ANALYSIS REQU	IRED	LAB ID
PSC 0703	water	VOA	40 ml	BTEX TPH-G- Ph		2826815
		V	70 11-		\	030 000 3
						-
	- 15 -	12/				
v .	_					
₹						
		-				
		W. "				
RELINQUISHED BY		DAT	E/TIME	RECEIVED BY	0 7-6	DATE / TIME
//4/5!/ach		7/3/96 2	10,000	- Thy	P 1-5-76	DATE/TIME
RELINQUISHED BY / 1/		' ' DAT	TE / TIME	RECEIVED BY LAB		DATE / TIME'
REMARKS				SHIPPED BY		

LABORATORY REPORT

Northwest Envirocon 7410 Deleware Lane Vancouver WA 98664

PROJECT NAME/SITE:

Detco

REPORT NUMBER:

17136

PROJECT NUMBER:

38-000002

REPORT DATE:

8-8-96

EXTRACTION DATE:

8-6-96

PAGES:

1 of 1

EPA 8020

Analyte: BTEX for water (Benzene, Toluene, Ethylbenzene, Xylenes)

Field ID	Lab ID	Identific	Surrogate			
		Benzene Toluene Ethyl- Xylen				Recovery (%)
				Benzene		7
DSC 0806	27324	ND	ND	ND	ND	116
BLANK	-	ND	ND	ND	ND	-
Quantification Limits	-	2	2	2	2	-

Surrogate is p-Bromofluorobenzene

ND = Not Detected (below reporting limit or detection limit)

TPH-G modified for water

Analyte: Total Petroleum Hydrocarbon Quantification

	·	(
Field ID	Lab ID	Matrix	μg/L (ppb)	
DSC 0806	27324	WATER	ND	Except to
BLANK	-	-	ND	
Detection Limit	-	-	125	

ND = Not Detected (below reporting limit or detection limit)

EPA 150.1 pH

Elit 180.1 pm			
Field ID	Lab ID	рН	
DSC 0806	27324	8.37	

REFERENCE MATERIAL DATE:

Report Number:	1	7	1	3	6

AUG - 9 1996

Environmental Sciences, Inc.

Research, Laboratory, and Consulting Services

CHAIN OF CUSTODY

2415 SE 11th Ave. • Portland, Oregon 97214 • (503) 231-9320 • FAX (503) 231-9344

PROJECT# 38-00002-	PROJECT I	VAME / SITE	3	STATE	PURCHASE OR	
COMPANY	REPORT A	TTENTION	F	PHONE NUMBER 340 699 4015	FAX NUMBER	11-632100
SAMPLES COLLECTED BY	DATE COLL	.ECTED	7	TIME COLLECTED 12:08 pm	SAMPLES CHIL	LED TO 4° C?
PRESERVATIVE USED? (HCl, etc.)						
FIELD ID	MEDIA	CONTAINER	VOLUME ET	C. ANALYSIS R	EQUIRED	LAB ID
DSC 0806	water	VOA	Youl	BTEX, TPH-G, P		27324
						IAL
						ATERIAL
						>
						EFERENCE
						2 (2)
RELINQUISHED BY		DAT	E / TIME -			
RELINQUISHED BY	l-	8/6/96	12:28 pm	RECEIVED BY		DATE / TIME
REMARKS		DAT	E/IIVIE F	REGEIVED BY LAB SMITHPED BY	8-6-9	DATE/TIME
				DINING BY		/

East will return white copy to client with laboratory report and keep yellow copy for files. Client keeps pink copy.

Date of Report: September 27, 1996 Samples Submitted: September 20, 1996 Lab Traveler: 09-047

Project: 38-000-002

EPA 602 & WTPH-G

Date Extracted: Date Analyzed:

9-26-96 9-26-96

Matrix: Water Units: ug/L (ppb)

Lab ID: Client ID: 09-047-9

DEL-DISCHARGE

Dilution Factor

	Result	Flags	PQL
Benzene	ND		1.0
Toluene	ND		1.0
Ethyl Benzene	ND	*	1.0
m,p-Xylene	ND	×	1.0
o-Xylene	ND		1.0
TPH-Gas	ND		100
Address of the second			

4-BFB

Surrogate Recovery 90%

Date of Report: September 27, 1996 Samples Submitted: September 20, 1996 Lab Traveler: 09-047

Project: 38-000-002

THE RESERVE AND A STREET

EPA 150.1

Date Analyzed: 9-20-96

Matrix: Water

pH Client ID Lab ID

8.48 DEL-DISCHARGE 09-047-1

Guain of Gustouy

-	/ /		. /-
Page	1	of	
· ago			

I KILKUSINEK

: 5UY-6Z/-5Zb5

'96 U8:24 P08

The state of the s		الماء	
	HUL		MG.

14924 NE 31st Circle • Redmond, WA 98052 Fax: (206) 885-4603 • Phone: (206) 883-3881

38-000-002

Delco/Milwaukie

Date

9-18

DATE

TIME

Sampled Sample

P. Trabusiner

Sample Identification

HN-DEL-10A

Northwest Envirocon

HW-DEL-10B HW-DEL- 11 A HW-DEL- 11B

HW-DEL- 12 A

HW-DEL- 12B

HW-DEL- 13A MW- JELS 133)FL-DISCHARGE

robusier

Company:

Project No:

Project Name:

Project Manager:

RELINQUICHED BY

RELINQUISHED BY

REVIEWED BY

NWE

FIRM

FIRM

Lab ID

GREAT TO THE COMMENT	urn Arou Requeste		Proj	ect C	hemi	st:	7	>P	>		La	bor	ato	ry A	lo.	>			à	Water to the second
1	Check Or	ne)								R	equ	este	d An	alys	is					
	Same	Day			7.				324						54					
	24 Hou	urs		.1					/8260/6						1904					
	48 Hou	urs							y 8240	625					150.1					
X	Standa	ard		,			0/624		tiles b	8270/	25	808	als (8)		1					
	(othe	r)	WTPH-HCID	WTPH-G/BTEX	0-	WTPH-418.1	Volatiles by 8240/624	Volatiles by 8260	Chlorinated Volatiles by 8240/8260/624	Semivolatiles by 8270/625	PAHs by 8270/625	PCB's by 8080/608	Total RCRA Metals (8)	TCLP Metals	H FRA	1				% Moisture
ne pled	Matrix	#of Cont.	WTP	WTPF	WTPH-D	WTPL	Volatil	Volatil	Chlori	Semiv	PAHS	PCB's	Total F	TCLP	0					% Mo
45	1/20	1		X															-	
45	- 4 -	1	-			ļ	-	ļ		1	_		-	-	-	-	-	-		_
32	-6 -	1	-	X			-		-	-	-	-	-	-	-	+	-	-	-	
32	-1 -)	+		-		+	-	-	-	-	-	-		-	-	-			-
30	74-	1		X	-	-	-	+	-	-	-	-	-	+-	+-	-	+			
30	-A -		-	-	-	-	-	-	-	-	+-	+	+-	+	+	+	-			
00		1	-	X	-	-	+	-	-	+	+	-	-	+	+	-	-			-
30	-k -	2	+	X	-		+	+			+	+	+	+	×		+			
				,						-	-	+		 						
						1 2					-									
				1																
CE VE		19	The	-	•	1	PATE 91	20	190	ے	001	MMEN	TS:							
BM C		Ot Tu	,,,,			1	TIME	00												
CEIVE	<i>>,</i> [€ O BY	Tu	VII	CL	,,		DATE													
RM			ii V		øn.	-	TIME			12										
ATE DE	VIEWED			Per Traffic Service						(Magazza (sedige	1									



Wy 'East Environmental Sciences, Inc.

LABORATORY REPORT

Northwest Envirocon 7410 Deleware Lane Vancouver WA 98664

PROJECT NAME/SITE:

Delco

REPORT NUMBER:

17692

PROJECT NUMBER:

38-000002

REPORT DATE:

10-30-96

EXTRACTION DATE:

10-29-96

PAGES:

1 of 1

EPA 8020

Analyte: BTEX for water (Benzene, Toluene, Ethylbenzene, Xylenes)

Field ID	Lah ID	Identific	Surrogate			
		Benzene	Toluene	Ethyl-	Xylenes	Recovery (%)
				Benzene		
DSC 1018	29155	ND	ND	ND	ND	98
BLANK	-	ND	ND	ND	ND	-
Quantification Limits	-	2.	2	2	2	-

Surrogate is p-Bromofluorobenzene

ND = Not Detected (below reporting limit or detection limit)

TPH-G modified for water

Analyte: Total Petroleum Hydrocarbon Quantification

Field ID	Lab ID	μg/L (ppb)	Surrogate Recovery (%)
DSC 1018	29155	ND	98
BLANK	-	ND	-
Detection Limit	-	125	_
ND = Not Detected (be	low reporting	limit or detecti	on limit)

EPA 9040 pH

Field ID	Lab ID	pН
DSC 1018	29155	7.71

Report Number:	
TEChor C Lightings	

Environmental Sciences, Inc.

17692
Research, Laboratory, and Consulting Services

CHAIN OF CUSTODY

2415 SE 11th Ave. • Portland, Oregon 97214 • (503) 231-9320 • FAX (503) 231-9344

					DUDOUACE OCO	CD#	
PROJECT#	PROJECT NAME / SITE		3	STATE OR	PURCHASE ORD	PURCHASE ORDER #	
38-000002	Dela	.3		OK	EAN AU IMPED		
COMPANY	REPORT A	TTENTION		PHONE NUMBER	FAX NUMBER	777	
NWE	Jef	/		360 699 4015 TIME COLLECTED	360 699 S	ED TO 1° C2	
SAMPLES COLLECTED BY	DATE COLLECTED			TIME COLLECTED		SAMPLES CHILLED TO 4° C?	
Jackum	10/18/	16		1:00 pm	yes		
PRESERVATIVE USED? (HCl, etc.)							
FIELD ID	MEDIA	CONTAINER	VOLUME ET	C. ANALYSIS	REQUIRED	LAB ID	
DSC 1018	water	VOA(2)	40 ml	13TEX 7911 G	Ph	29155	
0501018	Macco	Vo	707				
			2		17699		
			-				
•							
	= "						
		- E					
*							
RELINQUISHED BY			TE/TIME	RECEIVED BY		DATE / TIME DATE / TIME	
(lel)s(lah		1/24/9	TE / TIME	The state of the s	10-0	DATE / TIME	
RELINQUISHED BY		'DA	TE/TIME	RECEIVED BY LAB		DATETIME	
REMARKS				SHIPPED BY			
KEWAKKO			=				

WyEast will return white copy to client with laboratory report and keep yellow copy for files. Client keeps pink copy.

Appendix F

DELCO PROJECT

17873 S.E. McLoughlin BLVD Milwualkie, Oregon

Estimate of Discharge Volumes

Flow Rate: 7,200 gallons per day

Maximum Concentrations: Benzene = 0.00004 ppm

Toluene = 0.00000007 ppm Ethylbenzene = 0.017425 ppm Xylenes = 0.000371 ppm

Based on system efficiency calculations (enclosed) provided by the manufacturer, Environmental Products Northwest, Inc.

Note: The maximum concentrations were utilized to evaluate discharge concentrations. Too few data points are available to evaluate the average concentrations or discharge rates. Therefore, the maximum concentrations will serve as a conservative estimate of the average discharge concentrations and rates.

Calculation:

(flow rate - gal/day) (convert liters to gallons - l/gal) (discharge concentration - mg/l) (convert pounds to miligrams - lbs/mg) = pounds discharged per day - lbs/day

Benzene: 2.4×10^{-6} lbs/day (7,200 gal/day) (3.785 l/gal) (0.4*10⁻⁴ mg/l) (2.2*0⁻⁶ lbs/mg) = $2.4*10^{-6}$ lbs/day

Toluene: $4.2*10^{-9}$ lbs/day (7,200 gal/day) (3.785 l/gal) (7.0*10⁻⁸ mg/l) (2.2*10⁻⁶ lbs/mg) = $4.2*10^{-9}$ lbs/day

Ethylbenzene: $1.0*10^{-3}$ lbs/day (7,200 gal/day) (3.785 l/gal) (0.017425 mg/l) (2.2*10⁻⁶ lbs/mg) = $1.0*10^{-3}$ lbs/day

Xylenes: $2.2*10^{-5}$ lbs/day (7,200 gal/day) (3.785 l/gal) (3.71*10⁻⁴ mg/l) (2.2*10⁻⁶ lbs/mg) = $2.2*10^{-5}$ lbs/day

SCHEMATIC PROCESS FLOW

Ground Water Recovery Wells


2.5 gpm per well 5 gpm total combined flow 7,200 gallons per day total combined flow

Gasoline Product / Water Seperator

skims floating gasoline product 7,200 gallons per day

Diffused Aeration Stripper

extracts volatile dissolved gasoline constituents from water 7,200 gallons per day



DELCO PROJECT

17873 S.E. McLoughlin BLVD Milwualkie, Oregon

FIGURE

Prepared By:

Martin S. Burck Associates, Inc.



Permit Number: 1500A

Expiration Date: 6/30/2000

Page 1 of 4 Pages

GENERAL PERMIT

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

WASTE DISCHARGE PERMIT

Department of Environmental Quality 811 S.W. Sixth Avenue Portland, OR 97204 Telephone: (503) 229-5696

Issued pursuant to ORS 468B.050 and the Federal Clean Water Act.

ISSUED TO:

ISSUED 8/24/95 GEN15A

Clackamas/NWR OR004018-5

LUST# 03-93-008

Delco Petroleum Co., L.L.C.

14 Longleaf Dr

File No. 108705

Hamilton Square NJ 06890

Re: 17873 SE McLoughlin Blvd., Milwaukie OR

Wirbuel, Fining Michael Downs, Administrator

Water Quality Division

SOURCES COVERED BY THIS PERMIT:

Discharge of water contaminated with petroleum hydrocarbons from groundwater or surface water cleanup operations.

JULY 24, 1995

Date

PERMITTED ACTIVITIES

Until this permit expires or is modified or revoked, the permittee is authorized to construct approved waste water treatment and disposal systems and to discharge adequately treated waste waters only from the authorized discharge point or points established in Schedule A and only in conformance with all the requirements, limitations, and conditions set forth in the attached schedules as follows: Page

Schedule A - Waste Disposal Limitations	
Schedule B - Minimum Monitoring and Reporting Requirements 3	
Schedule B - William Monitoring and Repodules	
Schedule C - Compliance Conditions and Schedules	
Schedule D - Special Conditions 4	
General ConditionsAttach	led

Each other direct and indirect discharge of wastewaters is prohibited unless covered by another NPDES or WPCF permit.

Permit Number: 1500A Expiration Date: 6/30/2000 Page 2 of 4 Pages

SCHEDULE A

1. <u>Waste Discharge Limitations not to be Exceeded by Facilities Covered by this General Permit.</u>

When discharging to public waters:

Parameters Limitations TPH* Shall not exceed 1.0 mg/L Shall not exceed 0.25 mg/L Shall not exceed 0.025 mg/L Shall not exceed 0.025 mg/L Shall be within range 6.0 - 9.0

* TPH means total petroleum hydrocarbons. EPA method 418.1, or equivalent, shall be used for TPH analysis.

** BETX means the cumulative total of benzene, ethylbenzene, toluene, and xylenes. EPA method 8020, or equivalent, shall be used for these analyses.

2. The effluent limits set forth in paragraph 1 are based on a mixing zone that is defined as follows:

The allowable mixing zone shall not extend out into the stream more than one half the receiving stream width and shall not extend up or down the stream more than one receiving stream width. In no case shall the mixing zone extend beyond a radius of 10 meters from the point of discharge.

The discharge flow rate shall be regulated so as to provide at least a 10:1 dilution of the effluent at all times in the receiving stream.

3. Excluding the parameters for which effluent limits have been established by this permit, no wastes shall be discharged to surface waters and no activities shall be conducted which will violate Water Quality Standards as adopted in OAR Chapter 340 Division 41, except in the mixing zone as defined in paragraph 2 above.

Permit Number: 1500A Expiration Date: 6/30/2000 Page 3 of 4 Pages

SCHEDULE B

Minimum Monitoring and Reporting Requirements

Outfall Number 001 (the permittee shall sample in accordance with the following sampling frequency from start-up to six months after startup)

Item or Parameter M	inimum Frequency	Sample Type
Flow pH Total Petroleum Hydrocarbo Benzene BETX Lead**	Weekly* Weekly* ns Weekly* Weekly Weekly Monthly	Estimate Grab Grab Grab Grab Grab

* For the first five days of discharge, flow, pH, and total petroleum hydrocarbons (TPH) shall be measured daily.

Outfall Number 001 (the permittee shall sample in accordance with the following sampling frequency after six months from startup)

<u> Item or Parameter</u>	Minimum Frequency	Sample Type
Flow pH Total Petroleum Hydrocar Benzene BETX Lead**	Monthly Monthly bons Monthly Monthly Monthly Monthly Monthly	Estimate Grab Grab Grab Grab Grab

** The requirement to monitor for lead applies only to those facilities that are treating water contaminated with leaded fuels and where detectable levels of lead have been found in the influent to the treatment system.

Reporting Procedures

Monitoring results shall be reported on approved forms. The reporting period is the calendar month. Reports must be submitted to the Department by the 15th day of the following month.

Permit Number: 1500A Expiration Date: 6-30-2000 Page 4 of 4 Pages

SCHEDULE D

Special Conditions

- 1. A "contact person" shall be designated to coordinate and carry out all necessary functions related to maintenance and operation of waste collection, treatment, and disposal facilities.
- 2. All free product shall be removed and disposed in accordance with applicable rules.
- 3. Prior to the use of any storm sewer system, the permittee shall have written permission from the owner of the storm sewer.
- 4. The permittee shall notify the Department within 24 hours of any breakdown or failure of the treatment system or failure to meet the effluent limitations.
- 5. This permit applies only to facilities that discharge treated water from petroleum hydrocarbon cleanup operations and does not apply to any other cleanup operation.

1500A.new

NPDES GENERAL CONDITIONS

SECTION A. STANDARD CONDITIONS

1. Duty to Comply

The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of Oregon Revised Statutes (ORS) 468B.025 and is grounds for enforcement action; for permit termination, suspension, or modification; or for denial of a permit renewal application.

2. Penalties for Violations of Permit Conditions

Oregon Law (ORS 468.140) allows the Director to impose civil penalties up to \$10,000 per day for violation of a term, condition, or requirement of a permit.

In addition, Oregon Law (ORS 468B.990) classifies a willful or negligent violation of the terms of a permit or failure to get a permit as a misdemeanor and a person convicted thereof shall be punishable by a fine of not more than \$25,000 or by imprisonment for not more than one year, or by both. Each day of violation constitutes a separate offense.

3. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment. In addition, upon request of the Department, the permittee shall correct any adverse impact on the environment or human health resulting from noncompliance with this permit, including such accelerated or additional monitoring as necessary to determine the nature and impact of the noncomplying discharge.

4. Duty to Reapply

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and have the permit renewed. The application shall be submitted at least 180 days before the expiration date of this permit.

The Director may grant permission to submit an application less than 180 days in advance but no later than the permit expiration date.

5. Permit Actions

This permit may be modified, suspended, revoked and reissued, or terminated for cause including, but not limited to, the following:

- a. Violation of any term, condition, or requirement of this permit, a rule, or a statute;
- Obtaining this permit by misrepresentation or failure to disclose fully all material facts; or
- c. A change in any condition that requires either a temporary or permanent reduction or elimination of the authorized discharge.

The filing of a request by the permittee for a permit modification or a notification of planned changes or anticipated noncompliance, does not stay any permit condition.

6. Toxic Pollutants

The permittee shall comply with any applicable effluent standards or prohibitions established under Section 307(a) of the Clean Water Act for toxic pollutants within the time provided in the regulations that establish those standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.

7. Property Rights

The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.

8. Permit References

Except for effluent standards or prohibitions established under Section 307(a) of the Clean Water Act for toxic pollutants and standards for sewage sludge use or disposal established under Section 405(d) of the Clean Water Act, all rules and statutes referred to in this permit are those in effect on the date this permit is issued.

SECTION B. OPERATION AND MAINTENANCE OF POLLUTION CONTROLS

Proper Operation and Maintenance

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls, and appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of the permit.

2. Duty to Halt or Reduce Activity

For industrial or commercial facilities, upon reduction, loss, or failure of the treatment facility, the permittee shall, to the extent necessary to maintain compliance with its permit, control production or all discharges or both until the facility is restored or an alternative method of treatment is provided. This requirement applies, for example, when the primary source of power of the treatment facility fails or is reduced or lost. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

3. Bypass of Treatment Facilities

a. Definitions

- (1) "Bypass" means intentional diversion of waste streams from any portion of the treatment facility. The term "bypass" does not include nonuse of singular or multiple units or processes of a treatment works when the nonuse is insignificant to the quality and/or quantity of the effluent produced by the treatment works. The term "bypass" does not apply if the diversion does not cause effluent limitations to be exceeded, provided the diversion is to allow essential maintenance to assure efficient operation.
- (2) "Severe property damage" means substantial physical damage to property, damage to the treatment facilities or treatment processes which causes them to become inoperable, or substantial

and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.

- b. Prohibition of bypass.
 - (1) Bypass is prohibited unless:
 - (a) Bypass was necessary to prevent loss of life, personal injury, or severe property damage;
 - (b) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate backup equipment should have been installed in the exercise of reasonable engineering judgement to prevent a bypass which occurred during normal periods of equipment downtime or preventative maintenance; and
 - (c) The permittee submitted notices and requests as required under paragraph c of this section.
 - (2) The Director may approve an anticipated bypass, after considering its adverse effects and any alternatives to bypassing, when the Director determines that it will meet the three conditions listed above in paragraph b(1) of this section.
- Notice and request for bypass.
 - (1) Anticipated bypass. If the permittee knows in advance of the need for a bypass, it shall submit prior written notice, if possible at least ten days before the date of the bypass.
 - (2) Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in Section D, Paragraph D-5.

4. Upset

- a. Definition. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with technology based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operation error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventative maintenance, or careless or improper operation.
- b. Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology based permit effluent limitations if the requirements of Section B.4.c. of these General Conditions are met. No determination made during administrative review of claims that non-compliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.
- c. Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - (1) An upset occurred and that the permittee can identify the causes(s) of the upset;
 - (2) The permitted facility was at the time being properly operated; and

(3) The permittee submitted notice of the upset as required in Section D.5., hereof (24-hour notice).

- (4) The permittee complied with any remedial measures required under Section A.3 hereof.
- d. Burden of proof. In any enforcement proceeding the permittee seeking to establish the occurrence of an upset has the burden of proof.

5. Treatment of Single Operational Event

For purposes of this permit, A Single Operational Event which leads to simultaneous violations of more than one pollutant parameter shall be treated as a single violation. A single operational event is an exceptional incident which causes simultaneous, unintentional, unknowing (not the result of a knowing act or omission), temporary noncompliance with more than one Clean Water Act effluent discharge pollutant parameter. A single operational event does not include Clean Water Act violations involving discharge without an NPDES permit or noncompliance to the extent caused by improperly designed or inadequate treatment facilities. Each day of a single operational event is a violation.

6. Overflows from Wastewater Conveyance Systems and Associated Pump Stations

a. Definitions

- (1) "Overflow" means the diversion and discharge of waste streams from any portion of the wastewater conveyance system including pump stations, through a designed overflow device or structure, other than discharges to the wastewater treatment facility.
- "Severe property damage" means substantial physical damage to property, damage to the conveyance system or pump station which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of an overflow.
 - "Uncontrolled overflow" means the diversion of waste streams other than through a designed overflow device or structure, for example to overflowing manholes or overflowing into residences, commercial establishments, or industries that may be connected to a conveyance system.
- b. Prohibition of overflows. Overflows are prohibited unless:
 - (1) Overflows were unavoidable to prevent an uncontrolled overflow, loss of life, personal injury, or severe property damage;
 - (2) There were no feasible alternatives to the overflows, such as the use of auxiliary pumping or conveyance systems, or maximization of conveyance system storage; and
 - (3) The overflows are the result of an upset as defined in Condition B4 and meeting all requirements of this condition.
- c. Uncontrolled overflows are prohibited where wastewater is likely to escape or be carried into the waters of the State by any means.
- d. Reporting required. Unless otherwise specified in writing by the Department, all overflows and uncontrolled overflows must be reported orally to the Department within 24 hours from the time the permittee becomes aware of the overflow. Reporting procedures are described in more detail in Condition D.5.

7. Public Notification of Effluent Violation or Overflow

If effluent limitations specified in this permit are exceeded or an overflow occurs, upon request by the Department, the permittee shall take such steps as are necessary to alert the public about the extent and nature of the discharge. Such steps may include, but are not limited to, posting of the river at access points and other places, news releases, and paid announcements on radio and television.

8. Removed Substances

Solids, sludges, filter backwash, or other pollutants removed in the course of treatment or control of wastewaters shall be disposed of in such a manner as to prevent any pollutant from such materials from entering public waters, causing nuisance conditions, or creating a public health hazard.

SECTION C. MONITORING AND RECORDS

Representative Sampling

Sampling and measurements taken as required herein shall be representative of the volume and nature of the monitored discharge. All samples shall be taken at the monitoring points specified in this permit and shall be taken, unless otherwise specified, before the effluent joins or is diluted by any other waste stream, body of water, or substance. Monitoring points shall not be changed without notification to and the approval of the Director.

2. Flow Measurements

Appropriate flow measurement devices and methods consistent with accepted scientific practices shall be selected and used to insure the accuracy and reliability of measurements of the volume of monitored discharges. The devices shall be installed, calibrated and maintained to insure that the accuracy of the measurements is consistent with the accepted capability of that type of device. Devices selected shall be capable of measuring flows with a maximum deviation of less than \pm 10 percent from true discharge rates throughout the range of expected discharge volumes.

3. Monitoring Procedures

Monitoring must be conducted according to test procedures approved under 40 CFR Part 136, unless other test procedures have been specified in this permit.

4. Penalties of Tampering

The Clean Water Act provides that any person who falsifies, tampers with, or knowingly renders inaccurate, any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than two years, or by both. If a conviction of a person is for a violation committed after a first conviction of such person, punishment is a fine not more than \$20,000 per day of violation, or by imprisonment of not more than four years or both.

5. Reporting of Monitoring Results

Monitoring results shall be summarized each month on a Discharge Monitoring Report form approved by the Department. The reports shall be submitted monthly and are to be mailed, delivered or otherwise transmitted by the 15th day of the following month unless specifically approved otherwise in Schedule B of this permit.

6. Additional Monitoring by the Permittee

If the permittee monitors any pollutant more frequently than required by this permit, using test procedures approved under 40 CFR 136 or as specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR. Such increased frequency shall also be indicated. For a pollutant parameter that may be sampled more than once per day (e.g., Total Chlorine Residual), only the average daily value shall be recorded unless otherwise specified in this permit.

7. Averaging of Measurements

Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean, except for bacteria which shall be averaged based on a geometric or log mean.

8. Retention of Records

The permittee shall retain records of all monitoring information, including all calibration and maintenance records of all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample, measurement, report or application. This period may be extended by request of the Director at any time.

9. Records Contents

Records of monitoring information shall include:

- a. The date, exact place, time and methods of sampling or measurements;
- b. The individual(s) who performed the sampling or measurements;
- c. The date(s) analyses were performed;
- d. The individual(s) who performed the analyses;
- e. The analytical techniques or methods used; and
- f. The results of such analyses.

10. Inspection and Entry

The permittee shall allow the Director, or an authorized representative upon the presentation of credentials to:

- a. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
- b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- c. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit, and
- d. Sample or monitor at reasonable times, for the purpose of assuring permit compliance or as otherwise authorized by state law, any substances or parameters at any location.

SECTION D. REPORTING REQUIREMENTS

1. Planned Changes

The permittee shall comply with Oregon Administrative Rules (OAR) 340, Division 52, "Review of Plans and Specifications". Except where exempted under OAR 340-52, no construction, installation, or modification involving disposal systems, treatment works, sewerage systems, or common sewers shall be commenced until the plans and specifications are submitted to and approved by the Department. The permittee shall give notice to the Department as soon as possible of any planned physical alternations or additions to the permitted facility.

Anticipated Noncompliance

The permittee shall give advance notice to the Director of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

3. Transfers

This permit may be transferred to a new permittee provided the transferee acquires a property interest in the permitted activity and agrees in writing to fully comply with all the terms and conditions of the permit and the rules of the Commission. No permit shall be transferred to a third party without prior written approval from the Director. The permittee shall notify the Department when a transfer of property interest takes place.

4. <u>Compliance Schedule</u>

Reports of compliance or noncompliance with, or any progress reports on interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date. Any reports of noncompliance shall include the cause of noncompliance, any remedial actions taken, and the probability of meeting the next scheduled requirements.

5. Twenty-Four Hour Reporting

The permittee shall report any noncompliance which may endanger health or the environment. Any information shall be provided orally (by telephone) within 24 hours from the time the permittee becomes aware of the circumstances. During normal business hours, the Department's Regional office shall be called. Outside of normal business hours, the Department shall be contacted at 1-800-452-0311 (Oregon Accident Response System). A written submission shall also be provided within 5 days of the time the permittee becomes aware of the circumstances. The written submission shall contain:

- A description of the noncompliance and its cause;
- b. The period of noncompliance, including exact dates and times;
- c. The estimated time noncompliance is expected to continue if it has not been corrected; and
- d. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.
- Public notification steps taken, pursuant to General Condition B-7.

The following shall be included as information which must be reported within 24 hours under this paragraph:

a. Any unanticipated bypass which exceeds any effluent limitation in this permit.

- b. Any upset which exceeds any effluent limitation in the permit.
- c. Violation of maximum daily discharge limitation for any of the pollutants listed by the Director in the permit.

The Department may waive the written report on a case-by-case basis if the oral report has been received within 24 hours.

6. Other Noncompliance

The permittee shall report all instances of non-compliance not reported under Section D4 or D5, at the time monitoring reports are submitted. The reports shall contain:

- a. A description of the noncompliance and its cause;
- b. The period of noncompliance, including exact dates and times;
- c. The estimated time noncompliance is expected to continue if it has not been corrected; and
- d. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

7. Duty to Provide Information

The permittee shall furnish to the Department, within a reasonable time, any information which the Department may request to determine compliance with this permit. The permittee shall also furnish to the Department, upon request, copies of records required to be kept by this permit.

Other Information: When the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or any report to the Department, it shall promptly submit such facts or information.

8. Signatory Requirements

All applications, reports or information submitted to the Department shall be signed and certified in accordance with 40 CFR 122.22.

9. Falsification of Reports

State law provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or noncompliance shall, upon conviction be punished by a fine of not more than \$1,000 per violation, or by imprisonment for not more than six months per violation, or by both.

10. Changes to Indirect Dischargers - [Applicable to Publicly Owned Treatment Works (POTW) only]

The permittee must provide adequate notice to the Department of the following:

- a. Any new introduction of pollutants into the POTW from an indirect discharger which would be subject to section 301 or 306 of the Clean Water Act if it were directly discharging those pollutants and;
- b. Any substantial change in the volume or character of pollutants being introduced into the POTW by a source introducing pollutants into the POTW at the time of issuance of the permit.

c. For the purposes of this paragraph, adequate notice shall include information on (i) the quality and quantity of effluent introduced into the POTW, and (ii) any anticipated impact of the change on the quantity or quality of effluent to be discharged from the POTW.

SECTION E. DEFINITIONS

- BOD means five-day biochemical oxygen demand.
- TSS means total suspended solids (non-filterable residue).
- 3. Mg/l means milligrams per liter.
- 4. Kg means kilograms.
- 5. M³/d means cubic meters per day.
- 6. MGD means million gallons per day.
- Composite sample means a sample formed by collecting and mixing discrete samples taken periodically and based on time or flow.
- 8. FC means fecal coliform bacteria.
- 9. Technology based permit effluent limitations means technology-based treatment requirements as defined in 40 CFR 125.3, and concentration and mass load effluent limitations that are based on minimum design criteria specified in OAR 340-41.
- 10. CBOD means five day carbonaceous biochemical oxygen demand.
- Grab sample means an individual discrete sample collected over a period of time not to exceed 15 minutes.
- 12. Quarter means January through March, April through June, July through September, or October through December.
- 13. Month means calendar month.
- 14. Week means a calendar week of Sunday through Saturday.
- 15. Total residual chlorine means combined chlorine forms plus free residual chlorine.
- 16. The term "bacteria" includes but is not limited to fecal coliform bacteria, total coliform bacteria, and enterococci bacteria.
- 17. POTW means a publicly owned treatment works.

Appendix G

STATE OF OREGON MONITORING WELL REPORT (as required by ORS 537.765 & OAR 690-240-095)



	. MW.10	(6) LOCATION OF WELL By leg	al description	a	
Vamo Duender Dillon 3000	Grant Commence	Well Location: County CACAMA	S		18/
Address / Long Lext Dil	7io 08690	Township 25 (N or S) Range 20	(E or W)	Section_/	
	7. (10010	1. 5 1/4 of 1/4 2. Street address of well location 1/7/9/3	3 36 1116	lovih!	111
(2) TYPE OF WORK:		Milwauk P. OK.	1776		
New construction Repair	Recondition Abandonment	Tax lot number of well location ATTACH MAP WITH LOCATION ID	ENTIFIED	1.	
Conversion Deepening	Abandonment		ENTIFIED.		
(3) DRILLING METHOD Rotary Air Rotary Mud	7 Cable	(7) STATIC WATER LEVEL:	Date - 8-12	-56	
Hollow Stem Auger Other		Artesian Pressurelb/sq. in.	Date		
(4) BORE HOLE CONSTRUCTION	- Olor	The Mark Contract Day of the Property	or and third o	Ni	
Yes Wo	,	(8) WATER BEARING ZONES:			
Special Standards Depth of completed w		Depth at which water was first found		SWL	
in Villar R. Subrana Dopanianana	Land surface	From Strate To an wellst. Ho		3WL	,
Vault ft.				1 9	
_O_ft.	Water-tight cover		ana garasi	-	
70 \	Surface flush vault	control of sections are the Later of the			
"_ft. holes.∧P 	-Locking cap	il blanks a appealed to be every more			
	_Casing	(9) WELL LOG: Ground eleva	ation dayonds		
	diameter Old in.	Material		To	SWL
	Welded Threaded Glued	mod Bin Sharel	01	5	
		THE SAN SHOW	7	_	
Seal	Liner diameterin.	Browns gan Clay	5/	151	91
	materialm	_ man sing change	adria a tali		
	Welded Threaded Glued	1 23	**		
	Well seal: Material Fig. 1	4	a mora.		
	Amount 4 SACKS				
	Borehole diameter	14,	1999 C. C. C. C.		
	in.		- tr., , , , 1		
					John end
	Bentonite plug at least 2 ft. t	hick .	* 0. W 14		N. ma
	_ Screen		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	141	
Filter pack	material PUC				
A PAY	interval(s): From 10' To/5'		ort Home		
770	From To	a compared to the second secon		Adma Te	Marin P
	Slot size OlO in		7.14		
	- Filter pack: Material ALLA SANG				
	Size ///20 in.	Date started 8-17-56 C	completed 8/	2.96	
CENTER OF THE PERSON OF THE PE	7	(unbonded) Morritor Well Constructor Certifi	cation:		
(5) WELL TEST: make the remaindered by the	engele die land en	I certify that the work I performed on the	construction, alter		
Pump Bailer Air	Flowing Antesian	abandonment of this well is in compliance wi standards. Materials used and information re	ported above are	true to the	best
PermeabilityYield	GPM	knowledge and belief.			
Conductivity PH		Signed Sick DMCall	MWC Date	Number /	0316 R1
Temperature of water°F/C Depth artesia	an flow foundft.			18	16
Was water analysis done? Yes No		(bonded) Monitor Well Constructor Certifica I accept responsibility for the construction		andonmen	.t
By whom?	ft. toft.	work performed on this well during the const	ruction dates repo	orted above	e. All
Remarks:	rt.	work performed during this time is in compli- standards. This report is true to the best of n			truction
		/ \ -			COST
Name of supervising Geologist/Engineer Petal	yal-usiner	Signed Signed	Date_	1.1116	110
The second state of the se	A STREET OF THE PROPERTY OF TH				

STATE OF OREGON MONITORING WELL REPORT (as required by ORS 537.765 & OAR 690-240-095)			St	art Card #	900	56		
(1) OWNER/PROJECT: WELL NO. M. W. WELL NO. M. W. WELL NO. M. W. WELL NO. M. W.	w // (Well Lo	CATION	OF WE	LL By leg	al descript	1	
Address 14 Ling LPG+ DR.	08690	Townsh	ip 25	(N or S)	Range 1/4	(E or W	on.	18
(2) TYPE OF WORK: New construction Repair Record Repair Abar	ondition		HAR	A well locat	in Dorpudging	ENTIFIED.	_	
(3) DRILLING METHOD Rotary Air Rotary Mud Cable Hollow Stem Auger Other	e	(7) ST	TIC WA	TER LE	VEL:	Date	-12 %	5
(4) BORE HOLE CONSTRUCTIONS made would	c, rotary much, cable, in	is ynde	or ixod :	ARING	COMES:	D-III method		
Special Standards Depth of completed well	d surface	-	om	Toil	Est! Flo	w Rate 72 3	SW	
	er-tight cover		5	. 1011 1112	1 A	ر المارين المارين المارين المارين		
79 7 19	cing cap		algenia	rinks have 12.	, See [1]	Complete of)	
	meterin.	(9) WE	LL LOC		Ground eleva	From gay	То	SWL
	Ided Threaded Glued	1		in Hi	rela	05	6'	
1 4 42 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	er meterin. terial	Bi	ourse!	glag (May.	6'	151	9
	lded Threaded Glued				1	~2 4		
Well Mate	seal: Boot / Lyd		,		7.4 T. B.			
Bore	hole diameter in.					enga en grip	·F1	
$-\frac{1}{B_{\text{ent}}}$	onite plug at least 2 ft. thick		g-46	2111				
Filter			• •			21		- 1 2 B
pack inter	rial PVC val(s):							
Slot	nToin.	' '		-		t'> : \	•	
Mate	r pack: erial Sylve A SANC QUU-26n.	Date	started	X-17 C	/ 2 mil 6 mil	Completed_	217-6	506
(5) WELL TEST: Pump Bailer Air Permeability Yield Conductivity PH Temperature of water °F/C Depth artesian flow Was water analysis done? Yes No By whom? Depth of strata to be analyzed. From ft. to Remarks:	foundft.	I cert abandor standard knowle Signed (bonded I acc work pe	ify that the innent of this. Material dge and bell Monitor went response formed on a formed du	work I perform well is in construction with the second and in its second and in its second with the second and its second with the second and its second with the second and its second with the second with t	ctor Certificate construction ring the construction ring ring ring ring ring ring ring rin	Da ation: n, alteration, o truction dates iance with Ore my knowledge	alteration, or all construction are true to the VC Number tegen abandonm reported abandon well consumed and belief.	ent ove. All
Name of supervising Geologist/Engineer Polar Jack	Usings	Signed_	$\frac{1}{\sqrt{1}}$	11/5	Mile!	MV Da	VC Number	iw.

STATE OF OREGON MONITORING WELL REPORT (as required by ORS 537.765 & OAR 690-240-095) (6) LOCATION OF WELL By legal description WELL NO. M. IN (1) OWNER/PROJECT: Well Location County ClackAMAS 1 51236 218 Township 25 (N or S) Range 2E (E or W) Section 1/4 of above section __1/4 of _SU/ City Handler Souge 2. Street address of well location 17873 Milwoulkie M. 91267 (2) TYPE OF WORK: 3. Tax lot number of well location New construction Recondition Repair 4. ATTACH MAP WITH LOCATION IDENTIFIED. Abandonment Conversion Deepening (7) STATIC WATER LEVEL: SUZ-46 (3) DRILLING METHOD Rotary Air Rotary Mud Cable | Cable Artesian Pressure_ Hollow Stem Auger Other (3) Dall methodis: "Task the correction, when and halling hit (4) BORE HOLE CONSTRUCTION WORLD (8) WATER BEARING ZONES: Depth at which water was first found..... oecial Standards Depth of completed well SWL To Est. Flow Rate : 1 From ! > Land surface Water-tight cover -Surface flush vault The electrone Locking cap Ground elevation (9) WELL LOG: diameter From SWL Material material Welded Threaded Glued Liner Seal diameter material Welded Threaded Glued Amount Borehole diameter Bentonite plug at least 2 ft. thick miler / ft. Material SILVA Size 10/20 in. (unbonded) Monitor Well Constructor Certification: I certify that the work I performed on the construction, alteration, or (5) WELL TEST: abandonment of this well is in compliance with Oregon well construction Bailer Air Flowing Artesian Pump standards. Materials used and information reported above are true to the best knowledge and belief. Yield_ Permeability_ PH Conductivity °F/C Depth artesian flow found_ Temperature of water____ (bonded) Monitor Well Constructor Certification: Was water analysis done? Yes No I accept responsibility for the construction, alteration, or abandonment

Depth of strata to be analyzed. From____

Name of supervising Geologist/Enginee

Remarks:

ft. to

work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and belief.

	MWC Number
gned	Date
0	

WATER SAMPLING

JOB INFORMATION PROJECT NUMBER	الله الله الله الله الله الله الله الله	•
CLIENT	DELCO- MILWAUKIE	
DATE	9-17-96	
WEATHER	CLOUDY, COOL (50°)	
OPENED ALL WELLHEADS	Y65	

WELLHEAD INSPECT	ION
WELL ID NUMBER	MW-10-90055
LOCATION	LO4479 Water Resources Dept N ENTRANCE FROM MCGI.
SURFACE BOLTS	755
LID LOCKED	y 2 5
PRESSURE	No
GASKET	YES -OK
CAP ODOR	NO

HYDROLOGY MEASUREMENTS		
TIME	9:11	
FREE PRODUCT	No	
DTB	15'	
DTW	5' 2.5"	

#10

WELL DEVELOPMENT AND PURGING	
CASING DIAMETER	211
GALLONS/LINEAR FOOT	
11.0.1	MARKET TO ST. 10 1 1 1 2 2
PURGE (DTB-DTW)(GAL FT)(CASING VOLUMES)	
() () () () () () () () () ()	
PURGE START	9:18
PURGE STOP	9:27
ACTUAL PURGE	·
SAMPLING	() - 0/
DATE	9-17-96
22	

	ANALYSIS	AMOUNT	FILTER
MW-DEL-10A	0.000	402	No
MW-DEL-10B		402	NO

WATER SAMPLING

JOB INFORMATION	
PROJECT NUMBER	
CLIENT	DELCO - MILWAUKIE
DATE	9-17-96
WEATHER	CLOUDY, COOL (50°)
OPENED ALL WELLHEADS	VCS
CI ELLED TEED TEED TEED TEED TEED	182
· · · · · · · · · · · · · · · · · · ·	

WELLHEAD INSPECTION	ON .
WELL ID NUMBER	MW-11-90056
LOCATION	104488 - WATER RESOURCES # NW CORNER NEXT TO ED'S MUFFLE
SURFACE BOLTS	VES
LID LOCKED	·VES
PRESSURE	No
GASKET	OK
CAP ODOR	NO

HYDROLOGY MEASUREMENTS		
TIME	4:00	A Control of the Cont
FREE PRODUCT	NO	
DTB	15'	
DTW	6'6.5'	e e e e e e e e e e

WELL DEVELOPMENT AND PURGIN	<u>G</u> .
CASING DIAMETER 2 4	
O LL OVER DE LO FOOT	
GALLONS/LINEAR FOOT	
PURGE (DTB-DTW)(GAL FT)(CASING VOLUMES)	
PURGE START	9:00
PURGE STOP	9:10
ACTUAL PURGE	
SAMPLING DATE	9-17-96

SAMPLE	ANALYSIS	AMOUNT	FILTER
WDEL-114		402	10
MW-DEL-11B		402	no
A summer on the second			

WATER SAMPLING

JOB INFORMATION		
PROJECT NUMBER		
CLIENT	DELCO - MILWAUKIE	
DATE	9-18-96	
WEATHER	CLOUDY COOL (50°)	
OPENED ALL WELLHEADS	VES	
		100400
	YES	

WELLHEAD INSPECTI	ON
WELL ID NUMBER	MW-12-90057
	LO4489 WATER RESOURCES DEPT.
LOCATION	
	WEST SIDE
SURFACE BOLTS	YES
LID LOCKED	VE S
EID EOCKED	
PRESSURE	NO
GASKET	OK
CAP ODOR	NO

HYDROLOGY MEASUREMENTS		
TIME	9:00	
FREE PRODUCT	No	
DTB	15 /	
DTW	7 2 11 3/2	

#12

WELL DEVELOPMENT AND PURGING	
CASING DIAMETER	<i>L''</i>
GALLONS/LINEAR FOOT	
PURGE (DTB-DTW)(GAL FT)(CASING VOLUMES)	F
PURGE START	7:03
PURGE STOP	7:16
ACTUAL PURGE	
SAMPLING DATE	9-18-96

SAMPLE	ANALYSIS	. AMOUNT	FILTER
MII DEL-12A		400	NO
MW-DEL-12B		402	no.

WATER SAMPLING

recently and the second of	الأركنية بياسينيسيد
DELCO - MILWAUKIE	
9-18-96	
CLEAR, COOL 400	- ,
715	
	9-18-96

WELL ID NUMBER	MIV 15- 1213E,
LOCATION	LO4487 Water ROSOURUS SOUTH OF JIFT - JE
SURFACE BOLTS	Yes
LID LOCKED	Yes
PRESSURE	NO
GASKET	yes
CAP ODOR	/10

HYDROLOGY MEASUREMENTS		
TIME	7.00 A M	
FREE PRODUCT	NO.	
DTB	/5	
DTW	5/2.3"	

+13

WELL DEVELOPMENT AND PURGING	
CASING DIAMETER	
GALLONS/LINEAR FOOT	
PURGE (DTB-DTW)(GALFT)(CASING VOLUMES)	
PURGE START	7,25
PURGE STOP	7:40 Am
ACTUAL PURGE	
SAMPLING DATE	9-18-96

AMOUNT	FILTER
402	100
402	
/	700
	402

ENGINEERING & TECHNICAL SERVICES

Asbestos & Lead Inspections

Asbestos & Lead Abatement Project Design & Administration

Industrial Hygiene & Occupational Safety Services

Phase I Environmental Assessments

Site Characterizations

Environmental Remediation
Design, Testing & Reporting

Laboratory Analysis

CONSTRUCTION SERVICES

Asbestos & Lead Abatement

Facility Wrecking,
Dismantling & Demolition

Underground Storage Tank Removal

Mechanical Insulation

Offices Nationwide 1-800-625-7680