



**CITY of THE DALLES**  
313 COURT STREET  
THE DALLES, OREGON 97058

(541) 296-5481 ext. 1125  
COMMUNITY DEVELOPMENT DEPARTMENT

## SITE TEAM AGENDA

*The information contained in this agenda is for preliminary comments/concerns only.*

**Thursday, August 14, 2025, 1:00 p.m.**

***Please note: Applicant start time is 2:00 p.m.***

Meeting held via Zoom

<https://us06web.zoom.us/j/88316496257?pwd=VVdxVm5wQjRialdpOG9TdGFVeWF2QT09>

Meeting ID: **883 1649 6257** Passcode: **636603**

Dial: 1-669-900-6833 or 1-253-215-8782

### Action Items

*These items are for your review and comment. Please comment on or before the scheduled Site Team Meeting.*

- A. **ST 64-25: Marshal Sunshine 1 Inc** – Site Plan Review: The applicant is seeking to renovate the building (a gas station) to include convenience store and installation of gasoline pumps. The subject property is located at 1700 West 6<sup>th</sup> Street and further described as 2N 13E 33 C, Tax Lot 1900. The subject property is zoned CG – General Commercial.
- B. **ST 65-25: Mid-Columbia Forest Products** –Building Permit: Applicant is seeking to install a 40'x 80' metal building to store lumber. The subject property is located 2150 West 2<sup>nd</sup> Street and further described as 2N 13E 33 BC, Tax Lot 1200. The subject property is zoned CLI – Commercial / Light Industrial.
- C. **ST 66-25: Many Patel, Radhaji LLC** – Minor Partition Plat Review: Applicant requests a Minor Replat Partition to reconfigure the current diagonal property line bifurcating Tax Lots 200 and 300 with a new horizontal property line clearly distinguishing the parking lot on Tax Lot 200 from cinema structure on Tax Lot 300. The subject property is located at 2N 13E 32 A, tax lots 200 and 300. The subject property is zoned CG – General Commercial.

**Planner:** Sandy Freund, Sr. Planner

**Next regularly scheduled meeting: Thursday, August 28, 2025.**



**City of The Dalles**  
Community Development Dept.  
313 Court Street  
The Dalles, OR 97058  
(541) 296-5481, ext. 1125  
[www.thedalles.org](http://www.thedalles.org)

Site Team #: ST 64-25  
Received: 07/15/2025  
Filing Fee: \$100  
Receipt #: 875709  
Meeting Date: 08/14/2025

*Filing fee due with submittal*

## Site Team / Pre-Application Meeting

<input type="radio"/> Adjustment	<input type="radio"/> Mobile Home Park	<input type="radio"/> Conditional Use Permit	<input type="radio"/> Property Line Adjustment
<input type="radio"/> Building Permit	<input checked="" type="radio"/> Site Plan Review	<input type="radio"/> Minor Partition/Replat	<input type="radio"/> Planned Unit Development
<input type="radio"/> Variance	<input type="radio"/> Vacation (Street)	<input type="radio"/> Comp Plan Amendment	<input type="radio"/> Comp Plan/Zone Change
<input type="radio"/> Subdivision	<input type="radio"/> Zone Change	<input type="radio"/> Other: _____	

---

**Applicant**

Name: Marshal Sunshine 1 INC  
Address: 16020 Se 144th St Renton WA 98059

**Legal Owner (if other than Applicant)**

Name: Manjit Singh  
Address: 16020 Se 144th St Renton WA 98059

---

Phone #: 206-551-6200

Phone #: 206-551-6200

Email: keyinsurance20@outlook.com

Email: keyinsurance20@outlook.com

---

**Property Information**

Address: 1700 W 6th St The Dalles, OR

Map and Tax Lot: 2N 13E 33C 1900

---

**Project Description / Concept Plan** (continue on next page if necessary)


Renovation and addition to the existing building (gas station) and installing gasoline pumps. It is gas station and convenience store.

## Application Policy


I certify that I am the applicant or owner identified below. I acknowledge that the final approval by the City of The Dalles, if any, may result in restrictions, limitations, and construction obligations being imposed on this real property. I understand that if the property is owned in part or totality by a trust, partnership, corporation or LLC, I will be required to present legal documentation listing all persons that make-up the entity, as well as proof of my authorization to act on the entity's behalf. I consent and hereby authorize City representative(s) to enter upon my property for any purpose of examination or inspection related to this application. I certify that all information provided is true and correct, and consent to the filing of the application, authorized by my original signature below.

**The Site Team/Pre-Application meeting does not constitute an approved Land Use Application. The resulting Land Use Application must adhere to all applicable standards in effect at the time of application.**

Signature of Applicant



Signature of Property Owner



07/15/2025

Date

Date

### Department Use Only

City Limits:  Yes  No      Zone: \_\_\_\_\_      Overlay: \_\_\_\_\_      Airport Zone:  Yes  No

Geohazard Zone: \_\_\_\_\_      Flood Designation: \_\_\_\_\_

Historic Structure:  Yes  No      Current Use: \_\_\_\_\_

Previous Planning Actions:


Erosion Control Issues? Access Issues? Utilities and Public Improvements? Items Needing Attention?

# GAS STATION EXPANSION PROJECT


## 1700 W. 6TH STREET

## THE DALLES, OR.

## 97058



HOURS OF OPERATION  
(8AM-5PM)



### OCCUPANCY LOAD

LOCATION	OCCUPANCY RATIO	ACTUAL S.F.	OCCUPANCY RESULTS
CUSTOMER	1/60 S.F	2,000 S.F.	33
STORAGE	1/300 S.F	1,800 S.F.	6

### Square Footage

EXISTING BUILDING: 2,000 SF  
PROPOSED ADDITION 1,800 SF

OCCUPANCY: 39

### General Information

RENOVATION AND ADDITION TO AN EXISTING BUILDING.

PROJECT INFO:  
**GAS STATION EXPANSION PROJECT**  
1700 W. 6TH ST.  
THE DALLES, OR.  
97058  
PHONE# (541)500-1417


**EE DESIGNS**  
P.O. BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417

REVISIONS	DATE	PROJECT TITLE: GSEP			DRAWING TITLE: COVER SHEET			PROJECT NO: 2510
DESIGNED: XXX	CHECKED: XXX	REVIEWED: XX	DRAFTER: MPI	BUILDING NO:	FLOOR NO:	SHEET NO:		DATE: 6/09/2025

BUILDING CODE: 2023 O.S.S.C.  
OCCUPANCY CLASSIFICATION: M  
CONSTRUCTION TYPE: VB  
FIRE PROTECTION SYSTEM: NONE

Sheet No.	Sheet Title
A-0	COVER SHEET
A-1	DEMO PLAN
A-2	NOT USED
A-3	FOUNDATION PLAN
A-4	1st FLOOR PLAN
A-5	2nd FLOOR PLAN
A-6	EAST, WEST ELEVATIONS
A-7	NORTH, SOUTH ELEVATIONS
A-8	REFLECTED CEILING
A-9	DOOR SCHEDULE
A-10	DETAILS
A-11	DETAILS
C-1	SITE PLAN

## SCOPE OF WORK



## DEMO PLAN

1. Demo all interior non-structural walls as needed for the new floor plan.
2. Demo existing bathroom including fixtures and finishes.
3. Demo all damaged electrical equipment as needed for new floor plan.
4. Saw cut slab and pour back as needed for plumbing.
5. Replace existing man door on the north side of the building.
6. Demo and infill NW door
7. Demo ALL existing finishes through-out.
8. Infill existing storefront entrance with 6'-0-7'-0 double doors with side lights(field fit)  
(NO STRUCTURAL SCOPE)

## LEGEND

---

---

---

---




---

---

DEMO

PROJECT INFO:  
**GAS STATION  
EXPANSION PROJECT**  
**1700 W. 6TH ST.**  
**THE DALLAS, OR.**  
**97058**

**EE DESIGNS**  
P.O. BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417




**FOUNDATION PLAN**

PROJECT INFO:  
**GAS STATION EXPANSION PROJECT**  
1700 W. 6TH ST.  
THE DALLES, OR.  
97058


**EE DESIGNS**  
P.O. BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417

REVISIONS		DATE		PROJECT TITLE:			DRAWING TITLE:			PROJECT NO:	
				GSEP			FOUNDATION PLAN			2510	
				DESIGNED:	CHECKED:	REVIEWED:	DRAFTER:	BUILDING NO:	FLOOR NO:	SHEET NO:	
				XXX	XXX	XX	MPI				A-3



### LEGEND

- (1) ----- SOFFIT OPENING
- (2) ——— NEW
- (3) —— EXISTING
- (4) —— INFILL
- (5) ——— FUR (2X4 COLD MTL.)
- EGRES PATH



PROJECT INFO:  
**GAS STATION  
EXPANSION PROJECT**  
1700 W. 6TH STREET  
THE DALLES, OR.  
97058

**EE DESIGNS**  
P.O. BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417

REVISIONS  
DATE

PROJECT TITLE:  
**GSEP**



DRAWING TITLE:  
**2ND FLOOR PLAN**

PROJECT NO:  
**2510**  
DATE:  
**06/09/2025**

DESIGNED: XXX	CHECKED: XXX	REVIEWED: XX	DRAFTER: MPI	BUILDING NO:	FLOOR NO.: 2ND	SHEET NO: A-5
---------------	--------------	--------------	--------------	--------------	----------------	---------------

SCOPE OF WORK

1. Paint exterior (color/finish by owner—material to be contractor grade).
2. Install down spouts and gutters as needed.



PROJECT INFO:  
**GAS STATION  
EXPANSION PROJECT**  
1700w. 6th St.  
THE DALLES, OR.  
97058

**EE DESIGNS**  
P.O. BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417

REVISIONS

DATE

PROJECT TITLE:  
**GSEP**

DESIGNED:  
XXX

CHECKED:  
XXX


REVIEWED:  
XX

DRAFTER:  
MPI


DRAWING TITLE:  
**EAST/WEST  
ELEVATIONS**

PROJECT NO:  
**2510**  
DATE:  
**5/29/2025**

BUILDING NO:  
FLOOR NO:  
SHEET NO:  
**A-6**



**NORTH ELEVATION**



**SOUTH ELEVATION**

PROJECT INFO:  
**GAS STATION  
EXPANSION PROJECT**  
1700 W. 6TH STREET  
THE DALLES, OR.  
97058

**EE DESIGNS**  
P.O. BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417

REVISIONS

DATE

PROJECT TITLE:  
**GSEP**

DRAWING TITLE:  
**NORTH/SOUTH  
ELEVATIONS**

PROJECT NO:  
**2510**

DATE:  
**5/30/2025**

DESIGNED:  
XXX

CHECKED:  
XXX


REVIEWED:  
XX

DRAFTER:  
MPI


BUILDING NO:

FLOOR NO.:

SHEET NO:  
**A-7**



1ST FLOOR CEILING PLAN



SCALE: 1/4"=1'-0"

TYPE OF WORK


1. Install 2x2 Acoustical Ceiling Tile (ACT) and grids.
2. Install 2x2 interior high efficient LED lighting fixtures. (by owner)
3. Install 12"x48" L.E.D light fixtures(bathroom, kitchen and storage rooms.)(O.F.C.I.)

## NOTE


CEILING IN ACCORDANCE WITH OSSC, IBC  
AND LOCAL JURISDICTIONS.

## LEGEND


The diagram illustrates the internal structure of a light fixture. It features a central vertical line with horizontal dashed lines extending from it. The top dashed line is labeled 'A.C.T'. Below it is a horizontal line with a dotted pattern, labeled 'HARD LID'. Further down is a horizontal line with a grid pattern, labeled 'LIGHTING'. The bottom dashed line is labeled 'SOFFITTED OPENING'. A small vertical tick mark is positioned between the 'HARD LID' and 'LIGHTING' sections.




1  
A-10




2  
A-10



3/16"=1'0" **KITCHEN PREP ELEVATION**



POINT OF SALE ELEVATION




1  
A-10 TYPICAL (ADA) BATHROOM

2  
A-10 TYPICAL (ADA) BATHROOM

1  
SOMD: 3/16"=1'-0"  
3  
A-10  
TYPICAL (ADA) BATHROOM

NOTE:  
EQUIPMENT PERMITTED IN  
SHADeD AREA



## NWCB Technical Document

### SUSPENDED CEILINGS

#### 401

### Suspension Systems for Acoustical Lay-in Ceilings

#### Seismic Design Categories D, E & F

This document provides the 2021 IBC referenced standards for the prescriptive design and installation of suspension systems for acoustical lay-in ceilings. Incorporation of this document will provide a more uniform standard for installation and inspection. This document is intended to accomplish the intent of the International Building Code (IBC), including the Oregon Structural Specialty Code and Washington State Building Code, with regard to the requirements for seismic design category D, E and F for suspended ceilings and related items. Prescriptive suspension systems shall be installed per these requirements and those of the referenced documents. Engineered design of suspension systems are outside the scope of this document. Manufacturers' recommendations shall be followed where applicable.

The following are outside the scope of this technical document:

- Suspension systems for acoustical lay-in ceilings in Risk Category IV structures. *Source: ASCE 7 Section 13.1.3, ASTM E580 Section 5.7*
- Suspension systems for acoustical lay-in ceilings assigned a component importance factor of 1.5 in accordance with ASCE 7 Section 13.1.3 by the registered design professional. *Source: ASCE 7 Section 13.1.3, ASTM E580 Section 5.7*
- Suspension systems for acoustical lay-in ceiling designed in accordance with accepted engineering practice by a registered design professional. *Source: ASCE 7 Section 13.5.2*

#### General Requirements

- Referenced sources per hierarchy: 2021 International Building Code (IBC), American Society of Civil Engineers (ASCE-7-16), American Society of Testing Materials (ASTM C635, ASTM C636, ASTM E580).
- Partitions that are tied to the ceiling and all partitions greater than 6 ft in height shall be laterally braced to the structure. Bracing shall be independent of the ceiling splay bracing system. *Source: ASCE 7 Section 13.5.1.1*
- For further information on bracing of non-load bearing partitions, refer to NWCB Technical Document #200-501.
- All main beams are to be Heavy Duty (HD) as defined in ASTM C635. *Source: ASTM E580 Section 5.1.1*
- Ceilings less than or equal to 144 ft<sup>2</sup> and surrounded by walls or soffits that are laterally braced to the structure above are exempt from the seismic design requirements of ASCE 7 and ASTM E580. *Source: ASCE 7 Section 13.5.6.6*
- All wire ties shall be tightly wrapped around themselves a minimum of three turns within three inches (Figure 1).
- Source: ASTM C636 Section 2.3.4
- Main beams shall be level to within 1/4 in. in 10-ft. *Source: ASTM C636 Section 2.3.1*
- Cross tees shall be level to within 1/8 in. in 12-ft. *Source: ASTM C636 Section 2.2.1*

Build to a Higher Standard.

OREGON  
12437 NE 173rd Pl, Ste 200 | Woodinville, WA 98024  
tel 425-295-0333 | email info@nwcb.org

PAGE 1 OF 4

Figure 2: Lateral-Force Bracing. *Source: ASTM E580 Figure 3*

- Ceilings constructed of screw- or nail-attached gypsum board on one level that are surrounded by and connected to walls or soffits that are laterally braced to the structure above are exempt from seismic design requirements. *Source: ASCE 7 Section 13.5.6.6*

- Lateral-force bracing, which is the use of vertical struts (compression posts) and splay wires, is required for all ceiling areas greater than 1000 ft<sup>2</sup> (see Figure 2). *Source: ASTM E580 Section 5.2.8.7, Section 5.2.8.2*

- Lateral-force bracing shall be 12 ft on center (maximum) and begin no farther than 6 ft from walls. *Source: ASTM E580 Section 5.2.8.2*

- Lateral-force bracing splay wires shall consist of four 12-gauge wires attached to the main beam, arrayed 90° from each other and at an angle not exceeding 45° from the plane of the ceiling. *Source: ASTM E580 Section 5.2.8.2*

- Lateral-force bracing splay wires shall be attached to the grid and to the structure in such a manner that they can support a load of not less than 250 lb when tested per ASTM E3090 (Figure 6b). *Source: ASTM E580 Section 5.2.8.3*

- Power-actuated fasteners in concrete or masonry shall not be used for the attachment of lateral-force bracing splay wires unless tested and approved for seismic loading. *Source: ASCE 7 Section 13.4.5, Oregon Building Code Division 1 statewide Code Interpretation No. 11-01 (Oregon.gov/odot/codes-standards/documents/11-01-01.pdf#page=11)*

- Power-actuated fasteners in steel shall be permitted for the attachment of lateral-force bracing splay wires. *Source: ASCE 7 Section 13.4.6*

- Splay wires are to be within 2 inches of the connection of the vertical strut to suspended ceiling. *Source: ASTM E580 Section 5.2.8.4*

- Rigid bracing may be used in lieu of splay wires. *Source: ASTM E580 Section 5.2.8.4*

- Vertical struts must be positively attached to the suspension systems and the structure above. *Source: ASTM E580 Section 5.2.8.2*

- The vertical strut may be EMT conduit, metal studs or a proprietary compression post (see Figure 3).

- Changes in ceiling plane elevation requires independent lateral force-bracing for each ceiling plane. *Source: ASTM E580 Section 5.2.8.8*

#### Wall Moldings (Figures 4a and 4b)

- Wall moldings (perimeter closure angles) are required to have a horizontal flange not less than 2 inches wide. Two adjacent ends of the ceiling grid shall be positively attached to the wall molding (pop rivets or approved method), and the opposite ends shall have a 1/4 in. clearance from the wall and be free to slide. *Source: ASTM E580 Section 5.2.2.2, Section 5.2.3*
- Hanger wires shall be spaced 4-ft on center, maximum. *Source: ASTM C636 Table 2.1.3*
- Hanger wires shall be No. 12-gauge. *Source: ASTM C636 Section 2.1.6, ASTM E580 Section 5.2.7.1*
- Hanger wires shall not press against ducts or pipes. *Source: ASTM C636 Section 2.1.4*
- Where substantiating documentation has been provided to the local jurisdiction, proprietary perimeter clips may be used to satisfy the requirements for the 2-in closure angle.
- Hanger supporting clips shall be attached to the supporting closure angle or channel with a minimum of two screws per clip and shall be installed around the entire ceiling perimeter. *Source: ASCE 7 Section 13.5.6.2.29*

Source: ASTM C636 Section 2.3.3

Cross tees shall be level to within 1/4 in. in 10-ft. *Source: ASTM C636 Section 2.3.1*

Cross tees shall be level to within 1/8 in. in 12-ft. *Source: ASTM C636 Section 2.2.1*

Figure 3: Maximum Recommended Lengths for Vertical Struts

EMT CONDUIT	up to 5'10"
1/2" EMT conduit	up to 7'8"
1" EMT conduit	up to 9'9"
METAL STUDS	
Single 1 1/4" metal stud (20-gauge)	up to 12'0"
Back-to-back 1 1/4" metal stud (20 gauge)	up to 15'0"
Single 2 1/4" metal stud (20-gauge)	up to 13'0"
Back-to-back 2 1/4" metal stud (25-gauge)	up to 15'0"

Source: Northwest Wall and Ceiling Bureau

Note: Protrusions greater than 15° will require engineering calculations.

Figure 4a: Attached Wall Molding Requirements

Figure 4b: Unattached Wall Molding Requirements

Source: ASCE 7 Section 13.5.6.2.29

Figure 5a: Vertical-Strut Attachment


Source: ASCE 7 Section 13.5.6.2.29

Figure 5a: Vertical-Strut Attachment

Figure 5a: Vertical-Strut Attachment</

## KEYNOTES

- 1 EXISITING BUILDING 2,242 S.F.
- 2 PROPOSED ADDITION 1,486 S.F.
- 3 EXISITING FUEL ISLANDS (4)
- 4 EXISTING CONCRETE DRIVE SLAB
- 5 EXISTING CANOPY SUPPORTS (4)
- 6 EXISITING CONCRETE SIDEWALK
- 7 EXISTING ENTRY WAY (2)
- 8 DIRECTION ARROWS
- 9 EXISTING SIGNAGE
- 10 EXISTING PROPANE TANK
- 11 EXISTING LANDSCAPE
- 12 EXISTING CANOPY
- 13 EXISTING BOLLARDS
- 14 EXISTING CHAIN-LINK FENCING



## LEGEND

PROPERTY LINE	-----
SET BACK LINE	-----
EXISTING LANDSCAPE	.....
ASPHALT	.....
EXISTING CONCRETE	.....

PROJECT INFO:  
**GAS STATION  
EXPANSION PROJECT**  
**1700 W. 6TH ST.**  
**THE DALLAS, OR.**  
**97058**

**EE DESIGNS**  
P.O.BOX 3378  
CENTRAL POINT, OREGON 97218  
PHONE# (541)500-1417

		PROJECT TITLE: <b>GSEP</b>				DRAWING TITLE: <b>SITE PLAN</b>			PROJECT NO: <b>2510</b>
									DATE: <b>6/10/2025</b>
		DESIGNED: <b>XXX</b>	CHECKED: <b>XXX</b>	REVIEWED: <b>XX</b>	DRAFTER: <b>MPI</b>	BUILDING NO.:	FLOOR NO.:	SHEET NO: <b>C-1</b>	

# GAS STATION EXPANSION PROJECT

## 1700 W. 6TH STREET THE DALLES, OREGON

OCCUPANCY CLASSIFICATIONS	
CLASSIFICATIONS	TYPE
MERCANTILE	M

CONSTRUCTION	
WOOD FRAMED	V-B

PROPOSED EXPANSION TO AN EXISTING  
STORE/GAS STATION FACILITY.

STRUCTURAL DRAWINGS AND NOTES  
TAKE PRECEDENCE OVER OTHER DRAWINGS.

## GAS STATION EXPANSION PROJECT 1700 W. 6TH STREET THE DALLES, OREGON STRUCTURAL NOTES

### GENERAL

- The contract structural drawings and specifications represent the finished structure. They do not indicate the method of construction. The contractor shall provide all measures necessary to protect the structure during construction. Such measures shall include, but not be limited to bracing, shoring for loads due to construction equipment, etc. Observation visits to the site by the structural engineer shall not include inspection of the above items.
- The Contractor shall verify dimensions and all existing conditions shown on the drawings in the field and notify engineer of any discrepancies for correction or verification prior to construction of the affected work. The cost of additional design work due to errors or omissions in construction shall be borne by the contractor.
- Options are for the contractor's convenience. He shall be responsible for all changes necessary if he chooses an option and shall coordinate all details. The cost of additional design work necessitated by selection of an option shall be borne by the contractor.
- Establish and verify all openings and inserts for mechanical, electrical and plumbing with appropriate trades and the drawings.
- Provide all necessary temporary bracing, shoring, guying or other means to avoid excessive stresses and to hold structural elements in place during construction.
- Details on the drawings are typical. Verify all dimensions.
- Dimensions on the structural drawings are exact with the exception of masonry and sawn lumber dimensions which are nominal.
- See Architectural plans for exact location of windows and doors.
- Notes and details on drawings shall take precedence over general notes and typical details. Where no details are shown, construction shall conform to similar work on the project.
- Where reference is made to various test standards for materials, such standards shall be the latest edition and/or addendum.
- Construction materials shall be spread out if placed on framed floors or roof. Load shall not exceed the design live load per square foot.
- Drawings and specifications are instruments of service in respect to this specific project and are not intended or represented to be suitable for reuse on extensions of this project or on any other project. Any reuse without written verification or adaptation by Engineer will be at Owner's sole risk and without liability or legal exposure to Engineer. Owner shall indemnify and hold harmless Engineer from any and all claims, damages, losses and expenses including attorney's fees arising out of or resulting from unauthorized reuse.
- There are no intended third party beneficiaries.
- No changes from the approved structural plans shall be made in the field unless, prior to making changes, written approval is obtained from the Engineer. If changes are made without written approval such changes shall be the legal and financial responsibility of the contractor or sub-contractors involved and it shall be their responsibility to replace or repair the condition as directed by the Engineer.
- Engineering design provided by others and submitted for review shall bear the seal and signature of a Professional Engineer registered in Oregon.
- Use of these plans by the Contractor constitutes acceptance of these Notes and Conditions.

### STRUCTURAL NOTES

**CODES**  
16. 2022 Oregon Structural Specialties Code  
17. ACI 318-19

### DESIGN LOADS

Gravity Loads:  
a. Roof Dead Load 15 psf  
b. Roof Snow Load 25 psf  
c. Floor Dead Load 10 psf  
d. Office Floor Live Load 50 psf  
e. Storage Floor Live Load 125 psf

19. Lateral Loads:  
a. Wind: Speed 99 mph exposure B  
b. Seismic: Sds = 1.43 I = 1.0 Risk Category II Design Category D Site Class D

### FOUNDATIONS

- The foundation has been designed in accordance with the minimum design load listed in the 2019 OSSC. This foundation design is only for the referenced site and structure and shall not be used at any other location or for any other structure without express written consent of the structural engineer.

Allowable soil bearing pressures:

- Dead plus Live Loads : 1500 psf
- Subsurface peripheral drains shall be placed continuously around the perimeter of the foundation.
- The Contractor shall place all footings on undisturbed native soil or structural fill. The structural fill shall be moisture conditioned and compacted as specified below:
- Structural fill shall be non-expansive material relatively free of organic material with a maximum aggregate size smaller than 2 1/2" and at least 75% smaller than 3/4". On site materials are not suitable.
- Structural fill shall be compacted to 95 % density per ASTM D 698 at optimum moisture content. 10" maximum lifts.

28. Floor slab shall be placed on a minimum of 1" sand over 6" of relatively clean 3/4" minus granular fill over a 10 mil vapor barrier. All structural fill shall be moisture conditioned to within 2% of optimum moisture content and compacted to at least 95% of Standard Proctor density.

29. Prior to placing concrete slab on grade, the Contractor shall remove all decomposable materials and exposed surface shall be scarified to a depth of at least 6 inches and then be brought to the proper moisture content and compacted to the density specified below. Interior Slab Preparation:

30. Place foundation concrete only on clean, firm, inspected bearing material.

31. Ground surface shall be sloped to drain away from the structure in all directions at a slope of at least 12 inches in 10 feet and 2% thereafter. Roof downspouts, hose bibs and drains shall discharge well beyond the limits of the backfill. Proper surface drainage must be maintained for continued satisfactory foundation performance.

### CONCRETE

- Concrete has been designed and shall be constructed in accordance with the "Building Code Requirements for Reinforced Concrete", American Concrete Institute Standard 318-19 and Chapter 19 of the OSSC.
- All excavations shall be free of all loose material and water prior to placement of concrete.
- The engineer shall be notified at least 24 hours in advance of concrete placement so that he may compare reinforcement location with the intent of the design documents.
- Concrete work shall be in accordance with all requirements of ACI 301-10 Specifications for Structural Concrete for Buildings, ACI 302.1R-04 Guide for Concrete Floor and Slab Construction and OSSC Chapter 19, except as modified herein.
- Aggregate size: 1 1/2" maximum for footings, slabs 6 inches or more thick and other mass concrete and 3 1/4" for other concrete.
- No admixtures without approval. Admixtures containing chlorides shall not be used. Concrete shall not be in contact with aluminum.
- Do not place pipes, ducts, reglets or chases in structural concrete without approval of the Structural Engineer.

8. Concrete regular weight 144psf with Type II cement per ASTM C150, aggregate per ASTM C33, and potable water. Except as noted hereinafter, a maximum of 20% by weight of the total cementitious materials may be replaced by fly-ash, providing the fly-ash conforms to ASTM C618, Type F. The maximum proportion of fly ash in exterior concrete from December 1 to April 1 of the following year shall be 8% by

- Maximum air content shall conform to the following: 3%±1
- Maximum slump shall conform to the following: 4" to 5"
- Minimum 28-day compressive strength: 2,500 psi

### STRUCTURAL STEEL AND WELDS

- Latest AISC and AWS Codes and Handbooks shall apply. All structural steel has been designed and shall be fabricated and erected in accordance with the "Manual of Steel Construction", 13th Edition, published by the American Institute of Steel Construction.
- All steel plates and shapes shall conform to the following American Society for Testing and Materials, material designations:
  - Wide Flange Beams and Columns: ASTM A572, Fy= 50 ksi
  - Plates and Shapes: ASTM A36, Fy= 36 ksi
  - Pipes: ASTM A53, Grade B, Fy = 35 ksi
  - Structural Tubes: ASTM A500, Grade B, Fy = 46 ksi
- All welding and testing shall conform to the American Welding Society codes and recommendations. All welding shall be by welders holding current valid certificates and having current experience in type of weld specified. Certificates shall be those issued by an accepted testing agency.
  - Welding rods shall be low hydrogen E70, E60 when welding metal deck.
  - All welded splices in material thicker than 5/16" shall be inspected by an independent testing laboratory.

### REINFORCING

- All steel reinforcing bars shall be new billet steel in accordance with ASTM A615, Grade 60. Number 3 bars may be ASTM A615 - S1, Grade 40. Placement shall conform to ACI 301-10.
- All welded wire fabric shall be lapped one full mesh plus two inches and wired at sides and ends.
- Weld reinforcing bars in conformance with AWS DL4-79. Use low hydrogen electrodes.
- Reinforcing spacings given are maximum on center and all reinforcing is continuous unless otherwise noted.
- Provide bent corner reinforcing to match and lap with horizontal reinforcing at corners and intersections of walls, beams and footings per ACI Detailing Manual (ACI 315-05).
- Dowel all vertical reinforcing to foundations. Securely tie all reinforcing and embedded items in position before placing concrete or grout.
- Place reinforcing per ACI 318-19 and C.R.S.I. Standards.

### WOOD

- General
  - Each piece of lumber shall be S-DRY and bear the grade stamp of a grading rules agency approved by the American Lumber Standards Committee.
  - Each piece of lumber in place in the structure shall be of the original grade specified or better when inspected by a grading agency approved by the ALSC, regardless of required stamp and certifications.
  - Double floor joist under partitions.
  - Double studs at jambs and under beams.
  - Provide horizontal blocking at horizontal edges.
  - All structural timber framing, except pre-engineered manufactured roof trusses have been designed and shall be fabricated and erected in accordance with the "National Design Specification for Wood Construction", published by the National Forest Products Association and IBC Ch. 23.
- The Contractor shall take suitable precautions to accommodate drying shrinkage until volume loss is stabilized.
- Connections:
  - Any nailing not noted shall be according to Table 2304.9.1 of the International Building Code.
  - Make framed connections with approved framing anchors on each side or approved joist hangers by Simpson, Teco or K.C.
  - Pre-drill all holes for nails larger than 20d.
  - Field drill bolt holes for proper matching and bearings.
  - Provide cut washers at bolts in wood without steel plates.
  - Miscellaneous framing anchors shall be as manufactured by Simpson Company or other manufactured with current I.C.B.O. Approval.
  - Connect each roof truss to top plate with on Simpson H1 or equal, U.N.O.
- Structural Sawn Lumber shall be Douglas Fir - Larch, graded by either the Western Wood Products Association or the West Coast Lumber Inspectors Bureau, having the following grades unless noted otherwise on drawings:

GRADE	SPECIES
No. 2	Douglas Fir-Larch
No. 2	Douglas Fir-Larch
No. 1	Douglas Fir-Larch
No. 2	Douglas Fir-Larch
No. 1	Douglas Fir-Larch
No. 2	Douglas Fir-Larch
No. 2	Douglas Fir-Larch
No. 2	Douglas Fir-Larch

### 4. Glulam Beams:

- West Coast Douglas Fir (24F - V4) with Fb = 2,400 psi, Fv = 165 psi and E = 1,600,000 psi
- Fabrication and handling per latest AITC Standards. Each beam shall bear AITC stamp with certification.
- Fabricate with water resistant glue for interior conditions and waterproof glue for exposed conditions.
- See plans for required cambers.

### Scope of Special Inspections and Structural Observations

The following requires special inspections.

Excavated surface

Compacted fill if required - Each Lift

Welding - Prior to Painting

### DRAWING INDEX

S0.1 STRUCTURAL NOTES

S1.0 FOUNDATION PLAN

S2.0 FLOOR FRAMING PLAN

S3.0 ROOF FRAMING PLAN

S4.0 FOUNDATION DETAILS

S5.0 STRUCTURAL FRAMING DETAILS

S6.0 ROOF AND STAIR FRAMING DETAILS

### DRAWN:

BY: RH  
DATE: 06/25/2025

### CHECKED:

BY: SH  
DATE: 06/25/2025

### SCALE:

AS SHOWN


### PROJECT NO.:

10428

### SHEET NO.:

S0.1






1 FOUNDATION PLAN  
S1.0 SCALE: 1/4" = 1'-0"

S1.0 SCALE 1/4" = 1'-0"

<b>GAS STATION EXPANSION PROJECT</b>	
1700 W. 6TH STREET	
THE DALLES, OREGON	
<b>FOUNDATION PLAN</b>	
BY: <u>RH</u> DATE: <u>06/25/2025</u>	
CHECKED: BY: <u>SH</u> DATE: <u>06/25/2025</u>	
FILE: <u>1/4" = 1'-0"</u>	
PROJECT NO.: <u>10428</u>	
SET NO.: <u>S1.0</u>	




1 FLOOR FRAMING PLAN

S2.0 SCALE: 1/4" - 1'-0"

GAS STATION EXPANSION PROJECT  
1700W. 6TH STREET  
THE DALLES, OREGON  
FLOOR FRAMING PLAN

	DATE	REVISIONS
DRAWN:	△	△
BY:	RH	
DATE:	06/25/2025	
CHECKED:	△	△
BY:	SH	
DATE:	06/25/2025	
SCALE:	1/4" = 1'-0"	
PROJECT NO.:	10428	
SHEET NO.:	S2.0	

**HARVEY**  
**ENGINEERING, INC.**  
3000 NW Stewart Parkway, Suite 208  
Roseburg, OR 97471  
p (541) 236-7726 c (541) 817-9499




## TRUSS NOTES

1. TRUSS PROFILES ARE PROVIDED FOR GRAPHIC REPRESENTATION ONLY.
2. TRUSS PROFILES ARE TO CONFORM TO ROOF PROFILE AS NOTED ON THE PLANS.
3. TRUSSES ARE SPACED AT 2'-0" UNLESS NOTED OTHERWISE.
4. ALL TRUSS TO TRUSS CONNECTIONS SHALL BE DESIGNED BY THE TRUSS MANUFACTURER.
5. PROVIDE SEPERATE CAP TRUSS WHERE HEIGHT EXCEEDS TRANSPORT LIMITS.
6. TRUSS LOADS:

DEAD LOAD:	15 PSF	(9 PSF TOP CHORD - 6 PSF BOTTOM CHORD)
SNOW LOAD:	25 PSF	(TOP CHORD)
NET UPLIFT:	5 PSF	(TOP CHORD)

b. TRUSS LOADS:		
DEAD LOAD:	15 PSF	(9 PSF TOP CHORD - 6 PSF BOTTOM CHOR
SNOW LOAD:	25 PSF	(TOP CHORD)
NET UPLIFT:	5 PSF	(TOP CHORD)

## 2 TRUSS DIAGRAMS AND NOTES



1  
S3.0 ROOF FRAMING PLAN  
SCALE: 1/4" - 1'-0"

GAS STATION EXPANSION PROJECT  
1700 W. 6TH STREET  
THE DALLES, OREGON  
ROOF FRAMING PLAN

The logo for Harvey Engineering, Inc. It features the word "HARVEY" in a bold, blocky, all-caps font. To the left of "HARVEY" is a stylized graphic element consisting of a vertical line with a horizontal bar extending from its middle, and a shorter vertical line to its right, creating a shape reminiscent of a stylized 'H' or a valve component.

P(64) / 230 / 120 3(1) / 211 3122

MINIMUM REINFORCING BAR LAP SPLICE LENGTH	
BAR SIZE	LENGTH
#3	12"
#4	20"
#5	26"
#6	33"
#7	45"
#8	59"
#9	74"
#10	95"
#11	116"


MINIMUM REINFORCING BAR LAP SPLICE LENGTH	
CONDITION	COVER
CONCRETE CAST ON EARTH	3"
CONCRETE EXPOSED TO EARTH OR WEATHER	
#6 OR LARGER	2"
#5 OR SMALLER	1 1/2"
CONCRETE NOT EXPOSED TO EARTH OR WEATHER, SLABS, WALLS, OR JOISTS	
#14 OR #18	1 1/2"
#11 OR SMALLER	3/4"
BEAMS OR COLUMNS	1 1/2"

NOTE: SEE DRAWINGS FOR OTHER SPECIFIC COVER REQUIREMENTS


**1 STEEEL REINF. LAP AND COVER**

S4.0

SCALE: NA



STANDARD STIRRUP AND TIE HOOKS			
BAR SIZE	D (IN.)	90° HOOKS	135° HOOKS
#3	2 1/4"	3"	3"
#4	3"	4"	4"
#5	3 3/4"	5"	5"
#6	4 1/2"	6"	6"
#7	5 1/4"	7"	7"
#8	6"	8"	8"
#9	9"	10 1/8"	11 1/4"
#10	10"	11 1/4"	12 1/8"
#11	11"	12 3/8"	13 1/4"
#12	12 1/2"	1'0"	7 1/4"
#13	13 1/2"	1'2"	8 1/2"
#14	14 1/2"	1'7"	1'9"
#15	15 1/2"	1'11 1/2"	2'7 1/2"
#16	16 1/2"	1'13 1/2"	3'4 1/2"
#17	17 1/2"	1'15 1/2"	3'11 1/2"
#18	18 1/2"	1'17 1/2"	4'2 1/2"




STANDARD END HOOKS			
BAR SIZE	D (IN.)	180° HOOKS	90° HOOKS
#3	2 1/4"	3"	6"
#4	3"	4"	8"
#5	3 3/4"	5"	10"
#6	4 1/2"	6"	1'0"
#7	5 1/4"	7"	1'2"
#8	6"	8"	1'4"
#9	9"	10 1/8"	1'7 1/8"
#10	10"	11 1/4"	1'9 1/4"
#11	11"	12 3/8"	1'13 1/4"
#12	12 1/2"	1'0"	7 1/4"
#13	13 1/2"	1'2"	8 1/2"
#14	14 1/2"	1'7"	1'9"
#15	15 1/2"	1'11 1/2"	2'7 1/2"
#16	16 1/2"	1'13 1/2"	3'4 1/2"
#17	17 1/2"	1'15 1/2"	3'11 1/2"
#18	18 1/2"	1'17 1/2"	4'2 1/2"



NOTE: CONTRACTION CONTROL JOINTS ARE ONLY REQ'D AT AREAS SPECIFICALLY NOTED ON THE PLANS. JOINTS TO OCCUR AT SPACINGS OF 12' TO 15' ON CENTER EACH WAY.


CONTRACTION CONTROL JOINT



**4 INTERIOR FOOTING**

S4.0


SCALE: 1" = 1'-0"



**5 FOOTING AT (E) WALL**

S4.0


SCALE: 1" = 1'-0"



**6 EXT FOOTING**

S4.0


SCALE: 1" = 1'-0"



**7 SPREAD FOOTING**

S4.0

SCALE: 1" = 1'-0"



**8 BASE PLATE**

S4.0

SCALE: 3" = 1'-0"

**GAS STATION EXPANSION PROJECT**  
1700 W. 6TH STREET  
THE DALLES, OREGON  
FOUNDATION DETAILS

**HARVEY**  
ENGINEERING, INC.  
3000 NW Stewart Parkway, Suite 208  
Roseburg, OR 97471  
p (541) 236-7726 c (541) 817-9499

DRAWN: \_\_\_\_\_  
BY: \_\_\_\_\_ RH  
DATE: 06/25/2025  
CHECKED: \_\_\_\_\_  
BY: \_\_\_\_\_ SH  
DATE: 06/25/2025  
SCALE: \_\_\_\_\_  
AS SHOWN  
PROJECT NO.: 10428  
SHEET NO.: S4.0

**1** TYPICAL HEADER  
S5.0 SCALE: NTS

**2** TYP. TOP CHORD SPLICE  
S5.0 SCALE: 1" = 1'-0"

**3** TYPICAL SHEAR WALL  
S5.0 SCALE: NA

SHEAR WALL SCHEDULE					
MARK	SCHEATHING MATERIAL OR OSB	THICKNESS	EN (EDGE NAILING)	AB (ANCHOR BOLTS)	SILL PLATE NOMINAL THICKNESS
1	PLYWOOD OR OSB	7/16"	8d AT 6" O.C.	5/8d AT 48°	2x
2	PLYWOOD OR OSB	7/16"	8d AT 4" O.C.	5/8d AT 36°	2x

NOTE:  
1) FOR ITEMS NOT NOTED, SEE PLAN AND SHEAR WALL SCHEDULE  
2) MINIMUM PANEL DIMENSION IS 1'-0"  
3) USE FULL SIZE PANELS WHERE POSSIBLE  
4) FIELD NAILING (FN) AT 12" U.N.O.  
5) (2x) SOLID BLOCKING AT HORIZONTAL JOINTS

**4** SHEAR WALL SCHEDULE  
S5.0 SCALE: NA

**5** FLOOR FRAMING CONN  
S5.0 SCALE: 1" = 1'-0"


**6** FLOOR FRAMING CONN  
S5.0 SCALE: 1" = 1'-0"

**7** FRAMING CONN AT (E) BUILDING  
S5.0 SCALE: 1" = 1'-0"

**8** CONTINUOUS FLOOR FRAMING  
S5.0 SCALE: 1" = 1'-0"

**GAS STATION EXPANSION PROJECT**  
**1700 W. 6TH STREET**  
**THE DALLES, OREGON**  
**STRUCTURAL FRAMING DETAILS**

DRAWN:	BY: <u>RH</u> DATE: <u>06/25/2025</u>
CHECKED:	BY: <u>SH</u> DATE: <u>06/25/2025</u>
SCALE:	AS SHOWN
PROJECT NO.:	10428
SHEET NO.:	S5.0





**City of The Dalles**  
Community Development Dept.  
313 Court Street  
The Dalles, OR 97058  
(541) 296-5481, ext. 1125  
www.thedalles.org

Site Team #: ST 65-25  
Received: 07/16/2025  
Filing Fee: \$100  
Receipt #: 875711  
Meeting Date: 08/14/2025

## Site Team/Pre-Application Meeting

<input type="radio"/> Adjustment	<input type="radio"/> Mobile Home Park	<input type="radio"/> Conditional Use Permit	<input type="radio"/> Property Line Adjustment
<input checked="" type="radio"/> Building Permit	<input checked="" type="radio"/> Site Plan Review	<input type="radio"/> Minor Partition/Replat	<input type="radio"/> Planned Unit Development
<input type="radio"/> Variance	<input type="radio"/> Vacation (Street)	<input type="radio"/> Comp Plan Amendment	<input type="radio"/> Comp Plan/Zone Change
<input type="radio"/> Subdivision	<input type="radio"/> Zone Change	<input type="radio"/> Other: _____	

### Applicant

Name: Mrs. Columbia Forest Products  
Address: 2100 W 2<sup>nd</sup> St  
THE DALLES OR  
Phone #: 541-993-5961  
Email: midcolfp@gmail.com

### Legal Owner (if other than Applicant)

Name: GEORGE JOHNSON  
Address: 3370 Rachel Way  
Hood River 97081  
Phone #: 541-806-2212  
Email: gsj97031@gmail.com

### Property Information

Address: 2150 W. 2<sup>nd</sup> St, Map and Tax Lot: 2N 13E 53 BC 1200

### Project Description (continue on next page if necessary)

To install 1 - 40' x 80' WEB STEEL BOARDING (3200')  
intended to store lumber.

## Application Policy

I certify that I am the applicant or owner identified below. I acknowledge that the final approval by the City of The Dalles, if any, may result in restrictions, limitations, and construction obligations being imposed on this real property. I understand that if the property is owned in part or totality by a trust, partnership, corporation or LLC, I will be required to present legal documentation listing all persons that make-up the entity, as well as proof of my authorization to act on the entity's behalf. I consent and hereby authorize City representative(s) to enter upon my property for any purpose of examination or inspection related to this application. I certify that all information provided is true and correct, and consent to the filing of the application, authorized by my original signature below.

The Site Team/Pre-Application meeting does not constitute an approved Land Use Application. The resulting Land Use Application must adhere to all applicable standards in effect at the time of application.

Signature of Applicant

Signature of Property Owner

Matt McEll

7-7-25

Date

George S. Johnson

7-7-2

Date

### Department Use Only

City Limits:  Yes  No

Zone: \_\_\_\_\_

Overlay: \_\_\_\_\_

Airport Zone:  Yes  No

Geohazard Zone: \_\_\_\_\_

Flood Designation: \_\_\_\_\_


Historic Structure:  Yes  No

Current Use: \_\_\_\_\_

Previous Planning Actions:

Erosion Control Issues? Access Issues? Utilities and Public Improvements? Items Needing Attention?


Web Steel Buildings Northwest





60ft

-121.207 45.614 Degrees





**City of The Dalles**  
Community Development Dept.  
313 Court Street  
The Dalles, OR 97058  
(541) 296-5481, ext. 1125  
[www.thedalles.org](http://www.thedalles.org)

Site Team #: ST 66-25  
Received: 07/17/2025  
Filing Fee: \$100  
Receipt #: 875713  
Meeting Date: 08/14/2025

*Filing fee due with submittal*

## Site Team / Pre-Application Meeting

<input type="radio"/> Adjustment	<input type="radio"/> Mobile Home Park	<input type="radio"/> Conditional Use Permit	<input type="radio"/> Property Line Adjustment
<input type="radio"/> Building Permit	<input type="radio"/> Site Plan Review	<input checked="" type="radio"/> Minor Partition/Replat	<input type="radio"/> Planned Unit Development
<input type="radio"/> Variance	<input type="radio"/> Vacation (Street)	<input type="radio"/> Comp Plan Amendment	<input type="radio"/> Comp Plan/Zone Change
<input type="radio"/> Subdivision	<input type="radio"/> Zone Change	<input type="radio"/> Other: _____	

---

**Applicant**

Name: RADHAJI LLC  
Address: 2500 W 6TH ST  
THE DALLES OR 97058  
Phone #: 5413400664  
Email: PINALPLUS@YAHOO.COM

**Legal Owner (if other than Applicant)**

Name: MANNY PATEL  
Address: 2500 W 6TH ST  
THE DALLES OR 97058  
Phone #: 5413400664  
Email: PINALPLUS@YAHOO.COM

---

**Property Information**

Address: 2727 W 6TH ST TD

Map and Tax Lot: 02N13E32A 300

---


**Project Description / Concept Plan** (continue on next page if necessary)

## Application Policy

I certify that I am the applicant or owner identified below. I acknowledge that the final approval by the City of The Dalles, if any, may result in restrictions, limitations, and construction obligations being imposed on this real property. I understand that if the property is owned in part or totality by a trust, partnership, corporation or LLC, I will be required to present legal documentation listing all persons that make-up the entity, as well as proof of my authorization to act on the entity's behalf. I consent and hereby authorize City representative(s) to enter upon my property for any purpose of examination or inspection related to this application. I certify that all information provided is true and correct, and consent to the filing of the application, authorized by my original signature below.

**The Site Team/Pre-Application meeting does not constitute an approved Land Use Application. The resulting Land Use Application must adhere to all applicable standards in effect at the time of application.**


Signature of Applicant



7/9/25

Date

Signature of Property Owner



7/9/25

Date

### Department Use Only

City Limits:  Yes  No

Zone: \_\_\_\_\_

Overlay: \_\_\_\_\_

Airport Zone:  Yes  No

Geohazard Zone: \_\_\_\_\_


Flood Designation: \_\_\_\_\_

Historic Structure:  Yes  No

Current Use: \_\_\_\_\_

Previous Planning Actions:

Erosion Control Issues? Access Issues? Utilities and Public Improvements? Items Needing Attention?



To Whom It May Concern,

I am writing to request the division of parcel number 02N13E32A 300 from the curb line to create two distinct parcels:

- 0.94 acres (existing building)
- 1.08 acres (parking lot)

The existing building is currently unoccupied. Should it ever become occupied and require additional parking, we also control the adjacent lot, parcel number 2N13E32AD 1100, which can accommodate future parking needs.

Additionally, we are considering combining parcel number 02N13E32A 200 (0.57 acres) with the separated portion of parcel 300 to optimize the site's development potential.

Please advise on the steps required to process this request and any supporting documentation or maps you may need.

Thank you for your attention to this matter.

Sincerely,  
Manny Patel

541 3400664

[pinalplus@yahoo.com](mailto:pinalplus@yahoo.com)