

Amazon Data Services - PDX04 Data Center
AERMOD Input Data

Table D-2. Modeled Source Parameters

Gen Type	Source Type <i>SCRTP</i>	Source ID	UTM Easting	UTM Northing (m)	Elevation (m)	Stack Height <i>HGT</i> (m)	Temperature <i>TMP_1</i> (K)	Velocity <i>EXH_1</i> (m/s)	Exhaust Diameter <i>DIA</i> (m)
Type E	POINTHOR	B04_G13A	294041.8	5079913.31	91.04	5.16	682.93	35.474	0.51
Type E	POINTHOR	B04_G13B	294041.62	5079900.02	91.04	5.16	682.93	35.474	0.51
Type E	POINTHOR	B04_G14A	294041.47	5079889.2	91.04	5.16	682.93	35.474	0.51
Type E	POINTHOR	B04_G14B	294041.3	5079875.41	91.04	5.16	682.93	35.474	0.51
Type E	POINTHOR	B04_G15A	294040.77	5079841.57	91.04	5.16	682.93	35.474	0.51
Type E	POINTHOR	B04_G15B	294041	5079853.48	91.04	5.16	682.93	35.474	0.51
Type F	POINTHOR	B04_G15C	294041.15	5079866.71	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G16A	294040.72	5079833.67	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G16B	294040.54	5079819.85	91.04	5.16	763.82	45.589	0.51
Type G	POINT	B04_G17A	294040.14	5079789.98	91.04	5.91	778.15	41.445	0.51
Type G	POINT	B04_G17B	294039.99	5079780.98	91.04	5.91	778.15	41.445	0.51
Type G	POINT	B04_G17C	294039.91	5079774.1	91.04	5.91	778.15	41.445	0.51
Type F	POINTHOR	B04_G18A	294039.51	5079744.74	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G18B	294039.32	5079732.3	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G19A	294039.27	5079724.36	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G19B	294039.06	5079711.66	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G20A	294039.03	5079705.84	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B04_G20B	294038.77	5079692.88	91.04	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G01A	293729.55	5079709.11	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G01B	293721.79	5079709.21	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G02A	293750.52	5079708.89	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G02B	293742.77	5079708.99	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G03A	293763.43	5079708.77	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G03B	293771.49	5079708.65	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G04A	293791.86	5079708.39	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G04B	293784.5	5079708.53	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G04C	293805.37	5079708.23	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G05A	293865.97	5079707.61	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G05B	293872.3	5079707.5	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G05C	293859.49	5079707.67	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G06A	293892.59	5079707.23	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G06B	293886.16	5079707.32	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G07A	293909.34	5079707.03	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G07B	293916.01	5079706.91	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G08A	293935.44	5079706.79	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B52_G08B	293929	5079706.87	91.5	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G01A	293893.45	5079862.6	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G01B	293901.4	5079862.54	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G02A	293866.9	5079862.89	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G02B	293880.14	5079862.77	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G03A	293845.99	5079863.19	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G03B	293858.97	5079863	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G04A	293824.91	5079863.44	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G04B	293838.06	5079863.26	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G04C	293816.48	5079863.58	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G05A	293737.13	5079864.44	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G05B	293750.68	5079864.32	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G05C	293758.1	5079864.23	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G06A	293716.34	5079864.76	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G06B	293729.71	5079864.52	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B55_G07A	293695.54	5079864.93	90.59	5.16	763.82	45.589	0.51

Amazon Data Services - PDX04 Data Center
AERMOD Input Data

Table D-2. Modeled Source Parameters

Gen Type	Source Type <i>SCRTP</i>	Source ID	UTM Easting	UTM Northing (m)	Elevation (m)	Stack Height <i>HGT</i> (m)	Temperature <i>TMP_1</i> (K)	Velocity <i>EXH_1</i> (m/s)	Exhaust Diameter <i>DIA</i> (m)
Type F	POINTHOR	B55_G07B	293702.97	5079864.85	90.59	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G01A	293544.8	5079966.17	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G01B	293545.19	5079979.06	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G02A	293544.14	5079945.46	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G02B	293544.6	5079958.47	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G03A	293543.41	5079924.18	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G03B	293543.86	5079937.42	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G04A	293542.77	5079903.23	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G04B	293543.08	5079916.28	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G04C	293542.46	5079895.2	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G05A	293539.83	5079816.58	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G05B	293540.32	5079829.28	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G05C	293540.62	5079839.4	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G06A	293539.14	5079795.71	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G06B	293539.54	5079808.65	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G07A	293538.47	5079775.07	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G07B	293538.87	5079788	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G08A	293538.02	5079754.1	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B58_G08B	293538.34	5079767.13	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G01A	293661.76	5079761.05	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G01B	293661.34	5079748.27	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G02A	293662.32	5079783.1	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G02B	293662.03	5079770.09	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G03A	293663.15	5079803.51	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G03B	293662.8	5079790.6	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G04A	293663.83	5079824.43	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G04B	293663.47	5079811.47	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G04C	293664.01	5079833	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G05A	293666.65	5079911.71	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G05B	293666.13	5079898.92	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G05C	293666.06	5079890.79	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G06A	293667.31	5079932.88	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G06B	293666.93	5079919.59	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G07A	293667.99	5079954.1	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G07B	293667.41	5079940.46	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G08A	293668.26	5079973.29	89.58	5.16	763.82	45.589	0.51
Type F	POINTHOR	B61_G08B	293668.47	5079961.15	89.58	5.16	763.82	45.589	0.51
Type A	POINTHOR	P04_GEN1	293945.63	5079869.84	90.52	3.35	780.76	51.444	0.25
Type B	POINTHOR	P04_GEN2	293945.73	5079899.9	90.52	2.74	784.54	55.993	0.25
Type B	POINTHOR	P04_GEN3	293945.08	5079854.22	90.52	3.35	784.54	55.993	0.25
Type A	POINTHOR	P04_GEN4	293945.88	5079915.64	90.52	2.74	780.76	51.444	0.25
Type B	POINTHOR	P04_GEN5	293944.95	5079839.3	90.52	3.35	784.54	55.993	0.25
Type A	POINTHOR	P04_GEN6	293946.29	5079930.86	90.52	2.74	780.76	51.444	0.25
Type C	POINTHOR	P04_GENC	293933.64	5079887.2	90.52	3.35	749.55	38.329	0.36
Type H	POINT	SKILODG1	294073.48	5079830.16	91.12	1.91	726.09	56.149	0.25
Type I	POINT	SKILODG2	294105.99	5079789.67	91.74	6.71	675.71	55.761	0.36
Type D	POINTHOR	PORTABLE	293859.49	5079707.67	91.5	4.27	660.82	43.161	0.45